


TO SPECIFY

- Select the the cabinet dimensions, mounting style, door and frame material from the Buena Series chart below. The cabinet dimensions and mounting type are determined by the fire extinguisher size and wall depth available.
- Select the desired door style:
 - A Full Acrylic Door
 - E Full Acrylic Door with Scored Acrylic Insert and Cylinder Lock
- Optional: Select ¼" acrylic glazing material:
 - 16 Clear
 - 17 Bronze
 - 18 White
 - 19 Smoke
 - 20 Red
- Optional: Select lettering "Fire Extinguisher"

Horizontal	Vertical	Vertical Ascending
-HW ¹ White	-VW White	-VAW White
-HB Black	-VB Black	-VAB Black
-HR Red	-VR Red	-VAR Red
- Optional: Select lettering "Fire Dept. Valve":
 - WH White
 - BH Black
 - RH Red
- Optional Construction and Finishes:
 - FRC-** Fire-Rated Cabinets, add this prefix.
 - RR** Rolled Radius Frames, add this suffix.
 - RED** Red Polyester Finish, add this suffix.



Fire valve cabinets with a contemporary look— Like their fire extinguisher cabinet counterpart, Buena Series fire valve cabinets feature the ultra-clean, contemporary look of a full acrylic door, available in five eye-pleasing panel colors. Numerous lettering options make it easy to specify a truly modern, durable and functional fire valve cabinet.

SPECIFICATION

Valve/Fire extinguisher cabinet shall be Model No. _____ as manufactured by Potter Roemer, Santa Ana, CA, 800-366-FIRE. Install the cabinets plumb and level, where indicated on the drawings, at heights acceptable to the authority having jurisdiction. Each cabinet shall have a Potter Roemer Model No. _____ fire extinguisher installed inside.

SPECIFICATION EXAMPLE:

- 8120--A--16--RH--RED**
- 8120** - Cabinet Dimensions, Mounting and Material _____
 - A** - Door Style - Full Acrylic Panel _____
 - 16** - Acrylic Door Color - Clear _____
 - RH** - Optional Red Lettering - Red _____
 - Red** - Optional Finish - Red _____

MODEL NUMBER			WALL MOUNTING	BOX I.D.			FRAME O.D.		WALL OPENING			INLET LOC. SHELF			FRC OPTION			ADA	FOR USE WITH
STEEL	ALUMINUM	STAINLESS STEEL		K	L	M	N	O	W	H	D	Y	Z	Z-Z	W	H	D		
8120	8140	8160	Recessed-5/8	18	18	8	21 3/4	21 3/4	19	19	8 1/2	4	-	-	20 1/4	20	9 3/4	Yes	2 1/2" Angle Valve
8121	8141	8161	Trimless	18	18	8 3/4	21	21	19	19	9 1/4	9	4	-	20 1/4	20	10 1/2	Yes	
8122	8142	8162	Semi-Recessed-2	18	18	8	21 1/2	21 1/2	19	19	6 1/2	9	4	-	20 1/4	20	7 3/4	Yes	
8124	8144	8164	Surface	20	20	9 1/4	-	-	-	-	-	-	-	-	-	-	-	No	Up to 20 lb. Dry Chem. Fire Ext. and 2 1/2" Angle Valve
8125	8145	8165	Recessed-5/8	14	40	8	17 3/4	43 3/4	15	41	8 1/2	4	4	12	16 1/4	42	9 3/4	Yes	
8126	8146	8166	Trimless	14	40	8 3/4	17	43	15	41	9 1/4	4	4	12	16 1/4	42	10 1/2	Yes	
8127	8147	8167	Semi-Recessed-3	14	40	8	17 1/2	43 1/2	15	41	6 1/2	4	4	12	16 1/4	42	7 3/4	Yes	
8129	8149	8169	Surface	16	42	9 1/4	-	-	-	-	-	-	-	-	-	-	-	No	

All Dimensions In Inches