



# Hose Bibbs

125 PSI/8.6 Bar Non-Shock Cold Working Pressure to 100° F  
Maximum Temperature 180° F/82° C





## Quarter-Turn No-Kink Hose Bibb (Male or Cup to Hose) QT54X

Size	A		B		Weight	
	In.	mm.	In.	mm.	Lbs.	Kg.
1/2	3.15	.00	1.54	.00	.40	
3/4	3.15	.00	1.54	.00	.42	



## No-Kink Hose Bibb (Female to Hose) QT55X


Size	A		B		Weight	
	In.	mm.	In.	mm.	Lbs.	Kg.
1/2	2.87	.00	1.54	.00	.40	
3/4	3.15	.00	1.54	.00	.45	



## Hose Bibb (Male or Cup to Hose) 46-U

Size	B		Weight	
	In.	mm.	Lbs.	Kg.
1/2	2.06	52	.50	.23
3/4	2.06	52	.50	.23

46: 1/2 Cl 3/4 I 46-U: 1/2 Cl 3/4 I



## Garden Hose Valve/Inverted Neck Design (Female to Hose) 61

Size	B		Weight	
	In.	mm.	Lbs.	Kg.
1/2 Cl	3.63	92	.60	.27
3/4 I	3.75	95	.70	.32

