

Short Radius Monitors

Model	Height (in/mm)	Width (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	Outlet (in/mm)	GPM (GPM/LPM)
FP2SR-750	16 (406)	11 (279)	35 lbs	2-1/2 (64) flange	2-1/2 (64)	750 (2839)
FP3SR-750	22 (559)	13 (330)	45 (20)	3 (76) flange	2-1/2 (64)	750 (2839)
FP2SR(F/M)-750	16 (406)	11 (279)	35 lbs	2-1/2 (64) NPT - female or male	2-1/2 (64)	750 (2839)
FP3SR(F/M)-750	22 (559)	13 (330)	45 (20)	3 (76) NPT male or female	2-1/2 (64)	750 (2839)
FP3SR-1200	22 (559)	13 (330)	45 (20)	3 (76) flange	2-1/2 (64)	1,200 (4542)
FP4SR-1200	22 (559)	13 (330)	45 (20)	4 (102) flange	2-1/2 (64)	1,200 (4542)
FP3SR(F/M)-1200	22 (559)	13 (330)	45 (20)	3 (76) NPT male or female	2-1/2 (64)	1,200 (4542)

4" & 6" Station Monitors

4" (102mm) and 6" (152mm) diameter waterways are designed for applications that require large volumes of water with minimal manpower or friction loss. Large volume streams are ideally suited for breaking through thermal updrafts on tank fires, covering large areas quickly for vapor recovery, and for fireboat applications. Monitors can also be furnished with manifolds that are custom-built for specific requirements with Storz Quick Connect couplings 4" (102mm), 5" (127mm), or 6" (152mm) as required.

OPTIONS:

6" (152mm) discharge thread

2000 (7571) & 4000 (15142) GPM (LPM)

Detachable tiller bar handle with hitch pin

Vertical safety blade lock control

Greater flow capability with less friction loss



FP6-4000

2000-4000 GPM

Model	Height (in/mm)	Width (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	Outlet (in/mm)	GPM (GPM/LPM)
FP4-2000	32 (813)	22 (559)	135 lbs	4 (102) flange	4 (102)	2,000 (7571)
FP6-4000	44 (1118)	37 (940)	270 lbs	6 (152) flange	6 (152) waterway and 4 (102) NH male stainless steel discharge thread*	4,000 (15142)