


Bushings

Design Styles

The design style of most bushings is to have a solid wall between the inside and outside connections. Some of the multistep reductions with exceedingly thick cross-sections are not solid. This design style achieves structural support with a web of ribs attaching the inner and outer connection walls, with the open area toward the exterior bushing face. The styles are denoted by W and S for webbed and solid designs respectively.



Webbed design



Solid design


Chemtrol
Fig. No.

4518 Flush Socket Reducer Bushing (SPG x S) (cont.)

Nominal Size	Universal Part No.	Ctn. Qty.	Approx. Lbs./Ea.	Design Style	Dim. L _L	Dim. N _n
4 x 2	837-420	10	1.14	W	2.81	1.30
4 x 2 1/2	837-421	5	1.14	W	2.81	1.03
4 x 3	837-422	10	0.93	S	2.81	0.91
6 x 2	837-528	5	3.28	W	3.06	1.55
6 x 4	837-532	10	2.68	S	3.06	0.78
8 x 6	837-585	3	5.51	S	4.59	1.56
10 x 6	837-626	1	10.68	W	5.59	2.56
10 x 8	837-628	1	9.36	S	5.59	1.09
12 x 8	837-668	1	16.73	W	6.59	2.09
12 x 10	837-670	1	12.77	S	6.59	1.09

Other Reducing Couplings are produced by solvent cementing appropriate Reducer Bushings into Socket Couplings. They may be ordered as factory fabrications or may be assembled in the field.

4518-3 Flush Spigot x Thread Reducer Bushing (SPG x FPT)



Nominal Size	Universal Part No.	Ctn. Qty.	Approx. Lbs./Ea.	Design Style	Dim. L _L	Dim. Y*
1/2 x 1/4	838-072	50	0.03	S	1.17	0.31
3/4 x 1/4	838-098	50	0.04	S	1.29	0.31
3/4 x 1/2	838-101	50	0.03	S	1.29	0.43
1 x 1/2	838-130	50	0.07	S	1.56	0.43
1 x 3/4	838-131	50	0.05	S	1.56	0.45
1 1/4 x 1/2	838-166	10	0.14	S	1.66	0.43
1 1/4 x 3/4	838-167	10	0.12	S	1.66	0.45
1 1/4 x 1	838-168	10	0.10	S	1.66	0.53
1 1/2 x 1/2	838-209	25	0.12	W	1.53	0.64
1 1/2 x 3/4	838-210	25	0.10	S	1.53	0.52
1 1/2 x 1	838-211	25	0.08	S	1.53	0.39
1 1/2 x 1 1/4	838-212	10	0.06	S	1.53	0.27
2 x 1/2	838-247	25	0.25	S	1.66	0.77
2 x 3/4	838-248	25	0.25	S	1.66	0.65
2 x 1	838-249	25	0.25	W	1.66	0.52
2 x 1 1/4	838-250	10	0.22	W	1.66	0.40
2 x 1 1/2	838-251	25	0.20	W	1.66	0.27
2 1/2 x 1	838-289	10	0.31	W	1.94	0.80
2 1/2 x 1 1/4	838-290	10	0.31	W	1.94	0.68
2 1/2 x 1 1/2	838-291	10	0.27	S	1.94	0.55
2 1/2 x 2	838-292	10	0.24	S	1.94	0.43
3 x 1	838-335	10	0.65	W	2.42	1.28
3 x 1 1/2	838-337	10	0.67	W	2.42	1.03
3 x 2	838-338	10	0.64	S	2.42	0.91
3 x 2 1/2	838-339	10	0.48	S	2.42	0.64

Other size reductions are produced by solvent cementing appropriate Reducer Bushings together. They may be ordered as factory fabrications or may be assembled in the field.

*Typical male component engagement, hand tight (L₁ in ANSI B1.20.1 thread spec.) plus 1 1/2 turns.

Do not use or test the products in this catalog with compressed air or other gases.