Warm Air Hand Dryers





FB-740 Eclipse® SURFACE-MOUNTED HAND DRYER

Durable, drawn-steel white vitreous enamel cover, automatic sensor, *f* 115V AC, 20 Amp, 2300 Watts, 50/60 Hz, cULus Listed, or 208-240V AC, 9–10 Amp, 1900–2400 Watts, 50/60 Hz, cULus Listed, VDE approved, CE marked and CCC approved. Patented.






NEW

B-7128 TrimLineSeries ADA SURFACE-MOUNTED HAND DRYER

Durable, 18-gauge, type 304 satin-finish stainless steel cover with black plastic trim, automatic sensor, dual air outlets, *f*115V AC, 15 Amp, 1725 Watts, 50/60 Hz, Single Phase, cULus Listed, or 208-240V AC, 6.8-7.8 Amp, 1400-1900 Watts, 50/60 Hz, Single Phase, cULus Listed, VDE approved, and CE marked. Patent pending.





B-748 Eclipse Surface-Mounted HAND DRYER

Durable, drawn-steel bright-polished chrome-plated cover, automatic sensor, 115V AC, 20 Amp, 2300 Watts, 50/60 Hz, cULus Listed, or 208–240V AC, 9–10 Amp, 1900–2400 Watts, 50/60 Hz, cULus Listed, VDE approved, CE marked and CCC approved. Patented.






NEW

B-7120 TrimLineSeries ADA SURFACE-MOUNTED HAND DRYER

Durable, 22-gauge, zinc-plated steel with white epoxy cover with black plastic trim, automatic sensor, dual air outlets, *f*115V AC, 15 Amp, 1725 Watts, 50/60 Hz, Single Phase, cULus Listed, or 208-240V AC, 6.8-7.8 Amp, 1400-1900 Watts, 50/60 Hz, Single Phase, cULus Listed, VDE approved, and CE marked. Patent pending.



BOBRICK



FB-750 AirCraft® ADA RECESSED HAND DRYER

Durable, cast-iron with white vitreous enamel finish, automatic sensor, *f* 115V AC, 20 Amp, 2300 Watts, 50/60 Hz, cULus Listed, or 208–240V AC, 9–10 Amp, 1900–2400 Watts, 50/60 Hz, cULus Listed, VDE approved, CE marked and CCC approved.



Warm Air Hand Dryers



FB-708 AirGuard™SURFACE-MOUNTED HAND DRYER

Durable, cast-iron with white vitreous enamel cover, automatic sensor, £115V AC, 20 Amp, 2300 Watts, 50/60 Hz, cULus Listed.



- 8 STYLING, PERFORMANCE AND PRICING CHOICES.
- 6 DISTINCTIVE DESIGNS, 6 MATERIALS/FINISHES.
- 5 ELECTRONIC PLATFORMS.
- 5 VANDAL-RESISTANCE LEVELS.
- ENVIRONMENTALLY RESPONSIBLE; ELIMINATES PAPER TOWELS AND PAPER TOWEL DISPOSAL.
- SAVES 95% OF THE COST OF HAND DRYING.
- MINIMIZES THE INCIDENCE OF PAPER TOWELS BEING USED TO STOP UP TOILETS AND URINALS, AND THE COST OF REPAIR AND CLEAN-UP.



FB-700 AirCraft SURFACE-MOUNTED HAND DRYER

Cast-iron with white vitreous enamel finish, automatic (B-731, touch-button operation, 80-sec. drying cycle), f115V AC, 20 Amp, 2300 Watts, 50/60 Hz, cULus Listed, or 208–240V AC, 9–10 Amp, 1900–2400 Watts, 50/60 Hz, cULus Listed, VDE approved, CE marked and CCC approved.



DESIGNER'S NOTES:

- When ordering, specify voltage by adding 115V or 230V following model number, example: B-750 115V.
- 2. B-710 CompacDryer is not designed for vandal-prone installations. For vandal-prone installations, use Bobrick AirCraft and B-708 AirGuard dryers with cast-iron vitreous enamel finished covers, B-740 Eclipse dryer with drawn steel, vitreous enamel finished cover, or B-7128 TrimLine Dryer with satin-finish stainless steel cover.
- Bobrick automatic hand dryers should be installed 15" (380mm)
 above any projection or horizontal surface which may interfere with the
 operation of the automatic sensor.
- 4. Bobrick dryers comply with EU Directive "Restriction of Hazardous Substances" (RoHS) requirements for non-use of certain hazardous substances in the production of electronic products.



FB-710 CompacDryer™ SURFACE MOUNTED HAND DRYER

One-piece grey-molded plastic cover, automatic sensor, *f* 115V AC, 15 Amp, 1725 Watts, 60 Hz, cULus Listed. Patented.



WARRANTIES:

For product warranties and limitations information, see page 40.

