

GROUP 6 SPECIALTY AV PRODUCTS

NEW PIP-4 4 Composite Video Picture-in-Picture Inserter



The **PIP-4** is a high-performance picture-in-picture inserter for up to four composite video signals. The PIP output can display up to four images simultaneously each of which can be individually sized and positioned.

FEATURES

- **Picture-In-Picture Options** - All inputs can be displayed simultaneously, variable window sizing, variable window positioning, freeze frame capability. Quad button display 4 images in equal sizes
- **Multi-Format Operation** - s-Video and composite video outputs.
- **Multi-Standard Operation** - PAL & NTSC compatible inputs & outputs (no format conversion).
- **USB Mouse Connector** - For convenient navigation of the OSD.
- **Built-In ProcAmp** - Brightness, contrast, and saturation for each input.
- **Flexible Control Options** - Front panel, IR remote, mouse (with OSD), RS-232 & Ethernet.
- **Desktop Size** - Compact size. Two units can be rack mounted side-by-side in a 1U rack space with the optional RK-1 adapter.

NEW 912 Stereo Audio Power Amplifier (8.4 Watts per Channel)



The **912** is a high-performance power amplifier for balanced or unbalanced stereo audio signals. Either input can deliver a speaker output of 8.4 watts RMS power per channel into a 4Ω load.

FEATURES

- **Inputs** - 1 unbalanced stereo audio on RCA connectors, 1 balanced stereo on terminal block connectors.
- **Output** - Speakers on 4-pin terminal block connectors.
- **S/N Ratio** - 63dB balanced.
- **Volume Control** - Selectable control knob or 10V external control on a terminal block connector.
- **Indicator LEDs** - Power on, over temperature warning.
- **Compact Kramer TOOLS™** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

VS-40FW 4-Port FireWire® 800 Repeater/Hub



The **VS-40FW** is a high-performance bidirectional hub/repeater for 9-pin FireWire® 800 (IEEE 1394b) signals. It increases the number of ports available and/or extends the distance of FireWire® cable runs.

FEATURES

- **Ports** - 4 bidirectional IEEE 1394b 800Mbps (S800).
- **Range** - Doubles the cable range of FireWire
- **Hot Swapping** - Supports Plug and Play.
- **Transfer Rates** - 100, 200, 400 and 800Mbps.
- **ESD Protection** - Incorporates Kramer's Spark-Guard Pro™ signal protection circuitry to help protect against EDS (electrostatic discharge) that can damage digital equipment.
- **Alternate Power Sources** - Can be powered from the 12V DC power supply or through the PC connection.
- **Requires 9-Pin FireWire® 800 Cable.**
- **Compact Kramer DigiTOOLS®** - 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.

