









The 102xl is a high-performance 2-channel mono audio mixer for line level and mic level balanced audio signals. The unit mixes two mono inputs and produces a mixed audio output signal.

FEATURES

- S/N Ratio 91.5dB (line level), 62.5dB (mic level).
- Line or Mic Level Input selectable.
- Phantom Power 48V DC (input selectable).
- Level (Gain) Control Input 1, input 2, and master.
- Compact MultiTOOLS® 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-1 universal rack adapter.

TECHNICAL SPECIFICATIONS

INPUTS: 2 line/mic balanced mono on XLR (F) connectors.

OUTPUT: 1 line/mic balanced mono on a XLR (M) connector.

MAX. OUTPUT LEVEL: 18Vpp.
BANDWIDTH (-3dB): >100kHz.

S/N RATIO: Line: 91.5dB Mic: 62.5dB, 1kHz.

CONTROLS:
Line: <-48dB to +11.4dB, Mic: <-1.9dB to +62.5dB,
minimum to absolute gain. Phantom +48V selection
for condenser microphone by 90° DIP-switches;
Line/microphone input mode selection by 90°

DIP-switches.

COUPLING: Input: AC, Output: DC.
AUDIO THD + NOISE: Line: 0.013%, mic: 0.079%.
AUDIO 2nd HARMONIC: Line: 0.002%, mic: 0.01%.
POWER SOURCE: 12V DC, 112mA (DC).
DIMENSIONS: 10.68cm x 16.2cm x 4.2cm (4.2" x 6.38" x 1.65") W, D, H.
WEIGHT: 0.65kg (1.4lbs) approx.

ACCESSORIES: Power supply.

OPTIONS: RK-1 19" rack adapter.

