



Control4® Speakers

Control4® In-Ceiling Speakers (5.25", 6.5", 8")

The Control4 In-Ceiling Speaker line provides high-quality sound at an affordable price, and are ideal for multi-room audio systems.

Control4® In-Ceiling Stereo Speakers (6.5", 8")

Affordable, high-quality Control4® In-Ceiling Stereo Speakers are ideal for tight spaces where multiple speakers are not an option.

Control4® In-Wall Speakers (6.5", 8")

Control4® In-Wall Speakers provide high-quality sound at an affordable price, and are ideal for small theaters or rooms with unusually high ceilings.

Control4® Speakers

| | Control4® 5.25" In-Ceiling Speakers C4-IC5.25P | Control4® 6.5" In-Ceiling Speakers C4-IC6.5P | Control4® 8.0" In-Ceiling Speakers C4-IC8P | Control4® 6.5" In-Ceiling Stereo Speakers C4-SIC6.5S | Control4® 8.0" In-Ceiling Stereo Speakers C4-SIC8S | Control4® 6.5" In-Wall Speakers C4-IW6.5P | Control4® 8.0" In-Wall Speakers C4-IW8P |
|---|---|---|---|--|--|--|--|
| Woofers | | | | | | | |
| Infinite Baffle | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Voice Coil | 1" | 1" | 1" | 1" | 1" | 1" | 1" |
| Kapton(r) VC & Former | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Polymer Cone | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Tweeter | | | | | | | |
| Swivel Silk Soft Dome | 3/4" | 1" | 1" | N/A | N/A | 1" | 1" |
| Neodymium Magnet Drive | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Liquid Cooled | Yes | Yes | Yes | No | No | Yes | Yes |
| Specs | | | | | | | |
| Frequency Response | 58 Hz - 20 kHz +/- 3 dB | 58 Hz - 20 kHz +/- 3 dB | 48 Hz - 20 kHz +/- 3 dB | 58 Hz - 20 kHz +/- 3dB | 48 Hz - 20 kHz +/- 3 dB | 58 Hz - 20 kHz +/- 3 dB | 48 Hz - 20 kHz +/- 3 dB |
| Sensitivity | 87dB at 1m/1W | 88dB at 1m/1W | 88dB at 1m/1W | 88dB at 1m/1W | 88dB at 1m/1W | 88dB at 1m/1W | 88dB at 1m/1W |
| Minimum Power | 10 W | 15 W | 15 W | 15 W | 15 W | 15 W | 15 W |
| Maximum Power | 60 W | 80 W | 100 W | 80 W | 100 W | 80 W | 100 W |
| Nominal Impedance | 8 ohms | 8 ohms | 8 ohms | 8 ohms | 8 ohms | 8 ohms | 8 ohms |
| Cutout Dimensions | 6.44" diameter | 7.38" diameter | 8.63" diameter | 7.38" diameter | 8.63" diameter | 10.25" H x 7.25" W | 12.75" H x 8.69" W |
| Mounted Dimensions | 8" diameter | 8.5" diameter | 9.88" diameter | 8.5" diameter | 9.88" diameter | 12" H x 8.5" W | 14.13" H x 10" W |
| Engineering Features | | | | | | | |
| Open-Slope Composite Filter Engineering | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Field-Replaceable Tweeter | Yes | N/A | N/A | N/A | N/A | N/A | N/A |
| Gold-Plated Binding Posts | No | Yes | Yes | Yes | Yes | Yes | Yes |
| Speaker Wire Gauge Accepted | Up to 16 gauge | Up to 14 gauge | Up to 14 gauge | Up to 14 gauge | Up to 14 gauge | Up to 14 gauge | Up to 14 gauge |
| Mounting | | | | | | | |
| One-Piece Design | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Screw-Foot Pull-Down | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Paintable | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Grill and Mounting Hardware Included | Yes | Yes | Yes | Yes | Yes | Yes | Yes |

