105VB 1:5 Composite Video Distribution Amplifier






The 105VB is a high-performance distribution amplifier for composite video signals. It takes one input, provides correct buffering and isolation and distributes the signal to five identical outputs.

FEATURES

- Bandwidth 400MHz (-3dB).
- Connectors BNC (105V has RCAs).
- Level (Gain) Control.
- Compact Kramer TOOLS™ 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



TECHNICAL SPECIFICATIONS

INPUT: OUTPUTS:	1 composite video, $1Vpp/75\Omega$ on a BNC connector. 5 composite video, $1Vpp/75\Omega$ on BNC connectors.
MAX. VIDEO OUTPUT:	2Vpp.
VIDEO BANDWIDTH (-3dB):	400MHz.
DIFF. GAIN:	0.1%.
DIFF. PHASE:	O.1Deg.
K-FACTOR:	<0.05%.
S/N RATIO:	80dB.
CONTROL:	Up to +6dB.
COUPLING:	AC.
POWER SOURCE:	12V DC, 100mA.
DIMENSIONS:	12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98") W, D, H.
WEIGHT:	0.3kg (0.66lbs) approx.
ACCESSORIES:	Power supply, mounting bracket.
OPTIONS:	RK-3T 19" rack adapter.



1.34 KRAMER ELECTRONICS, Ltd DIRECTORY OF PRODUCTS 2011/2012 WWW.KRAMERELECTRONICS.COM

DISTRIBUTION AMPLIFIERS) ALL DISTRIBUTION AMPLIFIERS) CV (COMPOSITE VIDEO)