








The PT-102AN is a high-performance audio distribution amplifier for unbalanced stereo signals. The unit takes one stereo input and distributes the signal to two identical stereo outputs.

## FEATURES

- Level (Gain) Controls.
- S/N Ratio 85dB.
- Ultra Compact Pico TOOLSTM 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter.



## TECHNICAL SPECIFICATIONS

INPUT:
OUTPUTS:
MAX. OUTPUT LEVEL:
BANDWIDTH (-3dB):
S/N RATIO:
CONTROLS:
COUPLING:
AUDIO THD + NOISE:
AUDIO 2nd HARMONIC:
POWER SOURCE:

POWER SOURCE: DIMENSIONS:

WEIGHT: ACCESSORIES: OPTIONS: 1 unbalanced stereo audio on a 3.5mm mini jack. 2 unbalanced stereo audio on 3.5mm mini jacks.

5Vpp. >100kHz. 85dB @1kHz. Level: -55dB to +20dB. AC. 0.01% @1kHz.

O.01% @1kHz. O.004% @1kHz. 12V DC, 20mA.

6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H. 0.14kg (0.31lbs) approx.

ESSORIES: Power supply, mounting bracket. IONS: RK-4PT 19" rack adapter.

