






0 00000

The 102MX is a high-performance 2-channel stereo audio mixer for line level and mic level audio signals. It mixes one line level input with either a microphone or a second line level input and produces a mixed audio output signal.

## **FEATURES**

- S/N Ratio 69dB.
- Input Line level 1 (or microphone) and line level 2.
- Level (Gain) Control Line 1 (or microphone), line 2, and master level.
- Selectable Microphone Input Dynamic or condenser microphone with bias voltage.
- Talkover Button Microphone input signal mutes line audio output when a microphone detects sound.
- Compact Kramer TOOLS™ 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



## TECHNICAL SPECIFICATIONS

INPUTS: Mic/line 1:  $10\text{mV}/1.6\text{k}\Omega$ ,  $1\text{Vpp}/10\text{k}\Omega$ , on 6.5mm

phone connector; Line 2: 1Vpp/10kΩ, stereo on RCA

connectors.

OUTPUTS: Line level, stereo, up to  $5.6 Vpp/150 \Omega$  on RCA connectors.

BANDWIDTH (-3dB): 100kHz.

GAIN RANGE: -12dB to 68.5dB (mic); -12dB to +8.8dB (line 1).

DIFF. PHASE: 0.05Deg. S/N RATIO: 69dB.

CONTROL: Mic/line 1 level, line 2 level, master level rotary controls,

condenser/dynamic mic, line/mic, talkover selection

 switches.

 THD+NOISE:
 0.018%.

 2nd HARMONIC:
 0.002%.

 POWER SOURCE:
 12V DC, 40mA.

DIMENSIONS: 12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98") W, D, H.

WEIGHT: 0.25kg (0.55lbs) approx.
ACCESSORIES: Power supply, mounting bracket.
OPTIONS: RK-3T 19" rack adapter.

