








The VM-50HN is a high-performance distribution amplifier for headphone signals. It takes one stereo headphone input and distributes the signal to five identical stereo headphone outputs.

## **FEATURES**

- Input 1 6.5mm phone connector.
- Outputs 5 6.5mm phone connectors.
- Mono / Stereo Selector
- Level (Gain) Control Each output.
- Compact MultiTOOLS® 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-13 universal rack adapter.

## TECHNICAL SPECIFICATIONS



INPUT: 1 unbalanced stereo audio,  $1Vpp/50k\Omega$  on a

6.5mm phone jack.

OUTPUTS: 5 unbalanced stereo audio, 500mW/8 $\Omega$  on

6.5mm phone jacks. AUDIO BANDWIDTH (-3dB): 25kHz.

CONTROL: 5 stereo output level controls (front), 1 mono

switch (rear). -60dB to +10dB.

S/N RATIO: 78dB.

GAIN RANGE:

THD: 0.08% @100mW.
POWER SOURCE: 12V DC, 1A max.
DIMENSIONS: 16.5cm x 12cm x 4.5cm

(6.5" x 4.72" x 1.77") W, D, H. WEIGHT: 0.68kg (1.5lbs) approx.

ACCESSORIES: Power supply.

OPTIONS: RK-13 19" rack adapter.

