

The **VS-88H** is a high-performance matrix switcher for HDMI signals. It reclocks and equalizes the signal and can route any input to any or all outputs simultaneously.

## FEATURES

- Max. Data Rate 2.25Gbps per graphic channel.
- HDCP Compatible.
- HDTV Compatible.
- HDMI Support HDMI (V.1.4 with 3D, Deep Color, x.v.Color™, HDMI Uncompressed Audio Channels, Dolby TrueHD, DTS-HD).
- 3D Pass-Through.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems.
- Output Disconnect Each output.
- Front Panel Control Lockout.
- Memory Locations Stores multiple switches as presets to be recalled and executed when needed.
- Flexible Control Options Front panel, IR remote, RS-232 (K-Router™ Windows®-based software is included), Ethernet (Windows®-based Ethernet Configuration Manager & Virtual Serial Port Manager is included).
- Worldwide Power Supply 100-240V AC.
- Standard 19" Rack Mount Size 1U. Rack "ears" included.

## VS-88DVI 8x8 DVI Matrix Switcher



The **vs-88DVI** is a high-performance matrix switcher for DVI signals. The unit reclocks and equalizes the signal and can route any or all inputs to any or all outputs simultaneously.

## FEATURES

- Max. Data Rate 1.65Gbps.
- HDTV Compatible.
- Kramer Equalization & re-Klocking<sup>™</sup> Technology Rebuilds the digital signal integrity to travel longer distances.
- I-EDIDPro™ Kramer Intelligent EDID Processing™ Intelligent EDID handling & processing algorithm ensures Plug and Play operation for DVI systems.
- Flexible Control Options Front panel, IR remote, RS-232 (K-Router™ Windows®-based software is included), Ethernet (Windows®-based Ethernet Configuration Manager & Virtual Serial Port Manager is included).
- Output Disconnect Each output.
- Front Panel Lockout.
- Memory Locations Stores multiple switches as presets to be recalled and executed when needed.
- Worldwide Power Supply 100-240V AC.
- Standard 19" Rack Mount Size 2U. Rack "ears" included.

