








The PT-102SN is a high-performance video distribution amplifier for s-Video (Y/C) video signals. The unit takes one input, provides correct buffering and isolation, and distributes the signal to two identical outputs.

FEATURES

- Bandwidth (Y) 150MHz (-3dB).
- Y & C Level (Gain) Controls.
- Ultra Compact Pico TOOLS™ 4 units can be rack mounted sideby-side in a 1U rack space with the optional RK-4PT rack adapter.



TECHNICAL SPECIFICATIONS

INPUT: 1 s-Video on a 4-pin connector.

OUTPUTS: 2 s-Video on 4-pin connectors.

 MAX. OUTPUT LEVEL:
 1.3Vpp.

 BANDWIDTH (-3dB):
 150MHz.

 DIFF. GAIN:
 0.05%.

 DIFF. PHASE:
 0.05Deg.

 K-FACTOR:
 <0.05%.</td>

 S/N RATIO:
 76dB @5MHz.

CONTROLS: Gain: luma (Y) -1.9dB to +5.1dB; chroma (C) OdB

to +6.8dB, @5MHz.

COUPLING: AC.

POWER SOURCE: 12V DC, 25mA.
DIMENSIONS: 6.22cm x 5.18cm x 2.44cm

(2.45" x 2.04" x 0.96") W, D, H.
WEIGHT: 0.14kg (0.31lbs) approx.
ACCESSORIES: Power supply, mounting bracket.
OPTIONS: RK-4PT 19" rack adapter.

