




The 4x4A is a high-performance switcher for stereo audio signals. It switches any one of four input signals simultaneously to four identical outputs.

FEATURES

- S/N Ratio 90dB.
- Level (Gain) Control.
- Compact Kramer TOOLS™ 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.







TECHNICAL SPECIFICATIONS

OPTIONS:

INPUTS: 4 unbalanced stereo audio, $1Vpp/33k\Omega$ on 3.5mmmini jacks.

OUTPUTS: 4 unbalanced stereo audio, $1Vpp/220\Omega$ typical on

3.5mm mini jacks. MAX OUTPUT LEVEL: 5.2Vpp (+7dBu). AUDIO BANDWIDTH (-3dB): 100kHz. 90dB. S/N RATIO: -79dB @1kHz. CROSSTALK: 0.018%. THD @1kHz: 2nd HARMONIC: 0.002%.

POWER SOURCE: 12V DC, 20mA. DIMENSIONS: 12cm x 7.5cm x 2.5cm (4.7" x 2.95" x 0.98") W, D, H. 0.28kg (0.62lbs) approx. WFIGHT: ACCESSORIES: Power supply, mounting bracket. RK-3T 19" rack adapter.

> DIRECTORY OF PRODUCTS 2011/2012 WWW.KRAMERELECTRONICS.COM

