

WP-4iR

Active Wall Plate - Infrared Repeater



▲ European version



▲ US versions

The **WP-4iR** is an infrared signal repeater that can operate at distances up to 75m (240ft). The unit extends infrared signals into areas where there is no direct line-of-sight for normal infrared signal operation.

FEATURES

- Output - Up to 4 signals can be distributed to IR receivers.
- Wall Plate - 1 gang EU/US.

TECHNICAL SPECIFICATIONS

INPUT:	1 IR receiver.
OUTPUTS:	4 IR emitters on terminal block connectors.
POWER SOURCE:	12V DC, 95mA
DIMENSIONS:	USA: 6.9cm x 4.4cm x 11.4cm (2.72" x 1.74" x 4.5") W, D, H. Belgium and Germany: 8cm x 4.4cm x 8cm (3.15" x 1.74" x 3.15") W, D, H. UK and most of Europe: 8.6cm x 3.8cm x 8.6cm (3.39" x 1.74" x 3.39") W, D, H.
WEIGHT:	0.15kg (0.55lbs) approx.
ACCESSORIES:	Power supply, 3.5mm to IR emitter control cable (C-A35/IRE-10).
OPTIONS:	IR emitter control cable: C-A35/IRE-10` single emitter & C-A35/2IRE-10` dual emitter; 3.5mm extension cables: C-A35M/A35F-50` C-A35M/A35F-65`.

