






The VS-33Vxl is a high-performance switcher for composite video signals. Switching during the vertical interval ensures glitch-free switching with genlocked sources.

FEATURES

- Bandwidth 46MHz (-3dB).
- Vertical Interval Switching Genlocks to input 1.
- Contact Closure Remote Switching Capability.
- Compact Kramer TOOLS™ 3 units can be rack mounted side-by-side in a 1U rack space with the optional RK-3T rack adapter.



Composite

Player 3

Composite

Player 1

TECHNICAL SPECIFICATIONS

INPUTS: 3 composite video, $1\text{Vpp/}75\Omega$ on BNC connectors. OUTPUT: 1 composite video, $1Vpp/75\Omega$ on a BNC connector. MAX. VIDEO OUTPUT:

VIDEO BANDWIDTH (-3dB): 46MHz. DIFF. GAIN: 1.25%. DIFF. PHASE: O.5Deg. K-FACTOR: <0.05%. VIDEO S/N RATIO: 73dB.

SWITCHING: Vertical interval. CROSSTALK: -44dB @5MHz. POWER SOURCE: 5V DC, 22mA. DIMENSIONS:

12cm x 6.95cm x 2.44cm (4.72" x 2.74" x 0.96") W, D, H. 0.3kg (0.66lbs) approx. WEIGHT:

ACCESSORIES: Power supply.

RK-3T 19" rack adapter, OPTIONS:

VA-100P-5 5V DC power supply.



Composite

Recorder