

CP-GM (MR)

15-pin HD to RGBHV Style Bare End Installation Molded Plenum Cable



Kramer's **CP-GM (MR)** Series single-ended cables are constructed of plenum 5 mini coax cable. They come with a molded 15-pin HD connector already installed at one end, and a blunt cut at the other. They offer outstanding durability and high performance for any computer graphic video signal application where a plenum rating is required.

FEATURES

- **Plenum Rated** - The low smoke and fire-resistant properties of plenum rated cable allow it to reside in air return spaces of ceiling, floors, and walls, often saving the cost of installing conduit.
- **Quality Construction** - Constructed from flexible, high-quality plenum rated 5 mini coax cable.
- **Cable Specs** - See Kramer BCP-5X bulk cable for detailed specs.
- **Numerous Applications** - Perfect for applications requiring the cable fit into small conduit or other tight spaces before the bare end is terminated with 5 BNCs or another 15-pin HD connector. Ideal for routing typical computer video in professional A/V systems.
- **Varied Selection of Lengths** - Available in 15, 25, 35, 50, 75, 100, 125 and 150ft versions (1.8 to 45.7m).

CP-GM/5BM (M)

15-pin HD to 5 BNC Molded Plenum Breakout Cable



Kramer's **CP-GM/5BM (M)** series premium quality cables are constructed of plenum 5 mini coax cable terminated with a molded 15-pin HD connector at one end, and 5 BNCs at the other. They offer outstanding durability and high performance for any computer graphic video signal application where a plenum rating is required.

FEATURES

- **Plenum Rated** - The low smoke and fire-resistant properties of plenum rated cable allow it to reside in air return spaces of ceiling, floors, and walls, often saving the cost of installing conduit.
- **Quality Construction** - Constructed from flexible, high-quality plenum rated cable containing 5 mini coaxes. BNCs are premium quality true 75Ω.
- **Cable Specs** - See Kramer BCP-5X bulk cable for detailed specs.
- **Numerous Applications** - Ideal for applications requiring passive breakout from 15-pin to RGBHV. Ideal for routing typical computer video and audio signals in professional A/V systems.
- **Varied Selection of Lengths** - Available in 10, 15, 25, 35, 50, 75, 100, 125 and 150ft versions (3.0 to 45.7m).

CP-GM-XX-5BMKIT

15-pin HD to 5 BNC Plenum Breakout Cable Kit



Kramer's plenum breakout kits contain everything needed to build an attractive and high-quality 15-pin HD to 5 BNC breakout cable in the field.

FEATURES

- **Convenient Bundling** - Simplifies ordering and speeds up installation by bundling the right components into a single part number and package.
- **Kit Contents** - The kit contains a single-ended plenum VGA cable, five 75Ω crimp style male BNC connectors, color coded heat shrink for strain relief, a larger piece of heat shrink for the breakout point, and clear instructions.
- **Easy Installation** - Pull the single-ended cable into position so that the attractive molded 15-pin HD connector remains in the desired location, then prepare the bare end and install the crimp connectors using industry standard procedures and tools.
- **Plenum Rating** - The single-ended cable in any CP-GM-XX-5BMKIT is CL2P and CMP rated. It is constructed from Kramer BCP-5X cable which contains 5 high-resolution mini coaxes.
- **Varied Selection of Lengths** - Available in 10, 15, 25, 35, 50, 75, 100, 125 and 150ft versions (3.0 to 45.7m).

