








The VA-1DVIN is an EDID emulator for DVI-D signals. The unit can capture an EDID setting in non-volatile memory from the output allowing convenient and reliable connection to the source.

FEATURES

- Max. Data Rate 3.3Gbps.
- Input/Output DVI-D signals on DVI-I connectors. Passes analog signals on the DVI-I connector without processing.
- Control Capture button.
- Ultra-Compact PicoTOOLSTM 4 units can be rack mounted side by side in a 1U rack space with the optional RK-4PT rack adapter.



TECHNICAL SPECIFICATIONS

INPUT: 1 x DVI dual link, DVI 1.0, 1.2Vpp on a DVI Molex 24-pin

female connector; DDC signal 5Vpp (TTL).

OUTPUT: 1 x DVI, dual Link, DVI 1.0, 1.2Vpp on a DVI Molex 24-pin

female connector; DDC signal 5Vpp (TTL).

BANDWIDTH: 3.3Gbps.
CONTROLS: Capture EDID button.
POWER SOURCE: 5V DC, 20mA.

DIMENSIONS: 6.22cm x 5.24cm x 2.41cm (2.45" x 2.06" x 0.95") W, D, H.

WEIGHT: 0.15kg (0.55lbs) approx.

ACCESSORIES: Power supply

ACCESSORIES: Power supply.
OPTIONS: RK-4PT 19" rack adapter.

