

NPR NSR



**ELECTRIC 24/36 VOLT
REACH AND STRADDLE**
3000 / 3500 / 4000 / 4500 / 4500 / 5000 lbs.
(1350 / 1600 / 1800 / 2000 / 2000 / 2275 kg)

STANDARD SPECIFICATIONS

15D/17/20/22/22/25

Manufacturer's Designation		NPR 15D	NPR 17	NPR 20	NPR 22	NSR 22	NSR 25
Load Capacity / Rated Load @ 24" LC	lbs(kg)	3000 (1350)	3500 (1600)	4000 (1800)	4500 (2000)	4500 (2000)	5000 (2275)
Height Overhead Guard	in(mm)	95 (2413)	95 (2413)	95 (2413)	95 (2413)	95 (2413)	95 (2413)
Frame Width	in(mm)	40.25 (1022)	40.25 (1022)	40.25 (1022)	40.25 (1022)	40.25 (1022)	40.25 (1022)
Right Angle Stack (48" L x 40" W, Add 8" for Clearance)	in(mm)	106 (2692)	93.0 (2362)	93.0 (2362)	98.2 (2494)	93.0 (2362)	98.2 (2494)
Outside Turning Radius	in(mm)	76.14 (1934)	66.5 (1689)	66.5 (1689)	69.7 (1770)	66.5 (1690)	72.1 (1832)
Travel speed unloaded	mph (kph)	7.1 (11.4)	6.3 (10.1) / 7.2 (11.6)	6.3 (10.1) / 7.2 (11.6)	7.1 (11.4)	6.3 (10.1) / 7.2 (11.6)	7.1 (11.4)
Power Unit		36 volt	24 volt / 36 volt	24 volt / 36 volt	36 volt	24 volt / 36 volt	36 volt

STANDARD FEATURES

Transistor control • Sideshifter available • Various outrigger widths available • Drive-in rack overhead guards available • Variety of lights, alarms and other options are available



For more information on this model and the full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkmhc.com.