



# FasTrak™ Super Duty 48/54/60

## Features and Benefits

- Kawasaki and Honda Commercial V-twin engines
- 48", 54" or 60" side-discharge decks
- Welded steel decks. NOT STAMPED!
- 20" drive tires, 13" caster tires
- ZT 3100 Transmission
- Commercial duty, deck spindles
- Heavy-duty, 7-gauge, full-height rear bumper with built-in hitch provides protection for the engine and exhaust, retains the ease of maintenance.
- Toughest frame, front forks and deck in the industry
- Simplest maintenance in the industry
- 6.3-gallon fuel capacity with built-in sight line
- Seat springs and slide with arm rests come standard
- SmoothTrak™ steering with patented automatic park brake system
- Standard, foldable certified ROPS and seat belt.

LIMITED  
WARRANTY  
**4** YEAR | **800** HOUR  
RESIDENTIAL

LIMITED  
WARRANTY  
**2** YEAR | **800** HOUR  
COMMERCIAL

\* See your local Hustler dealer for complete warranty details



\* LIMITED \*  
**LIFETIME**  
**WARRANTY**  
FRAME & LEADING EDGE OF DECK

\* Original Purchaser Only

[hustlerturf.com](http://hustlerturf.com)

PN 601449 2-11

**HUSTLER**  
Cutting Grass Not Corners





# FasTrak™ Super Duty 48/54/60 Specifications

## Engines

<b>Kawasaki FX</b>	<b>Kawasaki FX</b>	<b>Honda GXV630</b>
24 hp	26 hp	

### More Engine Information:

• [www.kawpower.com](http://www.kawpower.com)

• [www.honda-engines.com](http://www.honda-engines.com)

### ENGINE

**Starter:** 12-volt (see engine manufacturer specs)

**Ignition:** Electronic

**Charging:** System 12-volt (see engine manufacturer specs)

**Fuel:** Unleaded gasoline - maximum of 10% ethanol in fuel (see engine manufacturer specs)

**Fuel Filter:** Replaceable, automotive-type

**Air Cleaner:** Heavy-duty, canister style

**Cooling:** Air cooled. Fly-wheel fan

**Governor:** Mechanical

### TRACTION DRIVE SYSTEM

**Type:** Dual hydrostatic. Hydro-Gear ZT 3100 commercial-duty pump/motor combination.

**Hydrostatic Drive:** V-belt drive from engine crankshaft

**Filter Spin-on type.**

### Ground Speed:

**Forward:** Infinitely variable: 0-8 mph (0-12.9 kph)

**Reverse:** 0-5 mph (0-8 kph)

**Steering:** SmoothTrak™ twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls

**Turning:** Radius True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels

### Brakes:

**Service:** Hydrostatic dynamic braking

**Parking:** Internal transmission mechanical brake. When steering levers are placed in neutral position, integral park brakes are automatically engaged

### Tires:

**Front:** 13 x 5 – 6, rib tread

**Drive:** 48 in: 20 x 10 – 10, turf tread

54 in: 20 x 12 – 10, turf tread

60 in: 20 x 12 – 10, turf tread

### Capacities:

**Fuel System:** 6.3 US gal (23.84 l)

### GENERAL INFORMATION

**Safety Features:** Operator presence system connected to deck and drive clutches. Stabilizer rollers at rear of tractor

**Seat:** Molded-vinyl seat with adjustable armrests. Fore and aft sliding adjustment. Seat-pan suspension springs standard.

**Construction:** Mainframe is 1.5 in x 1.5 in x .188 in (3.8 cm x 3.8 cm x .48 cm) square steel tubing. Front caster wheels mounted with roller bearings on each wheel. Front caster forks are .375 in (.95 cm) steel

**Controls:** Hand-operated choke/throttle, ignition switch, electric mower clutch. Integrated parking brakes

**Indicators:** Hour meter, engine warning light (low oil pressure)

**Cup Holder:** Two cup holders molded into the left side fuel tank. Accommodates nearly any cup size.

### DIMENSIONS

**Height:** 41.8 in (106.17 cm)

#### W/48 in Deck:

**Length:** 74.42 in (189.02 cm)

**Overall width:** 50.3 in (127.7 cm) w/discharge chute up

**Tire-to-tire width:** 47 in (119.38 cm)

**Weight:** 835 lbs (378 kg)

#### W/54 in Deck:

**Length:** 74.42 in (189.02 cm)

**Overall width:** 56.2 in (142.7 cm) w/discharge chute up

**Tire-to-tire width:** 51 in (129.54 cm)

**Weight:** 860 lbs (390 kg)

#### W/60 in Deck:

**Length:** 75.92 in (193 cm)

**Overall width:** 62.7 in (159.26 cm) w/discharge chute up

**Tire-to-tire width:** 51 in (129.54 cm)

**Weight:** 885 lbs (401 kg)

### DECKS

**Side-Discharge:** 48", 54" or 60"

**Type:** Free-floating deck using three blades with center blade to the front. Deck is suspended at the corners.

Includes 4 deck-mounted rollers to improve flotation in rolling and uneven terrain

**Construction:** 11 ga, .120 (.30 cm) welded steel with 11

ga, .120 in (.30 cm) doubler welded onto spindle mount areas. Solid 1 in x .375 (2.55 cm x .95 cm) steel bars reinforce impact areas on trim edges. Commercial-style box-section reinforced front edge.

**Cutting Heights:** Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (3.81 cm to 11.43 cm)

**Mowing Blades:** Heavy-duty, heat-treated, high-lift steel

48 in: 16.5 in x 2.5 in x .20 in

54 in: 18.5 in x 2.5 in x .20 in

60 in: 20.5 in x 2.5 in x .20 in

**Blade Tip Speed:** (at 3600 RPM engine speed)

48 in: 18,600 fpm

54 in: 18,910 fpm

60 in: 18,410 fpm

**Deck Drive:** V-belt drive to all three spindles. Spring tension idler for extended belt life.

**Spindle:** Aluminum casting with steel shafts and sealed ball bearings.

**Discharge Chute:** High density, rubberized

### Width of Cut:

48 in: 47.1 in (120 cm)

54 in: 53.1 in (135 cm)

60 in: 59.1 in (150 cm)

**Trim Capacity:** (left side)

48 in: 0.5 in (1.25 cm)

54 in: 2.5 in (6.5 cm)

60 in: 5.9 in (15 cm)

### ACCESSORIES

**2-Bag Catcher:** Commercial-duty, 7.2 bushel, rear-mounted, two-bag catcher

**Mulch Kit:** Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

**Flex Forks™:** Shock-absorbing front caster forks for a smooth ride and smoother cut

**Other Accessories:** Light Kit, Stripe Kit, Steering Lever Extension Kit

*Specifications subject to change without notice.*