



REFUSE & RECYCLING BODY COMPANY

CURB MASTER SERIES

Non FET / Non CDL Side Loader



Cart Tipper Option



*Side Dump Plastics and
Cardboard Compactor Options
Are Available For Collection Of
Second Commodity*

KANN Manufacturing Corporation

210 Regent Street
PO Box 400
Guttenberg IA 52052 0400

Tel (563) 252 2035

Fax (563) 252 3069

E-mail sales@kannmfg.com

Web www.kannmfg.com

04/2006

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



REFUSE & RECYCLING BODY COMPANY

CURB MASTER SERIES

Non FET / Non CDL Side Loader



FEATURES

FUNCTIONS

- 10-12 SEC trough cycle
- 37 SEC compactor cycle
- 45-50 SEC body eject
- Pack-on-the-go

GENERAL

- 15 or 20 YD³ body capacity including tailgate
- 2.7 YD³ hopper capacity
- 97 IN body height above frame (trough down)
- 113 IN single lid height (low profile) above frame with trough up
- 130 IN lid height (single or dual trough) above frame with trough up
- 96 IN body width
- 28 FT² (4.3 FT x 6.5 FT) hopper opening
- 700 LB trough lift capacity
- Up to 700 LB/YD³ payload
- 0.42 YD³ trough capacity for single or dual troughs
- 4-6 IN trough loading height below chassis frame; approximately 29-34 IN from ground to top of trough edge
- Standard curb side trough
- Manual controls
- PTO driven pump with overspeed control
- Tailgate ajar/overheight, trough overheight, and hydraulic overheat alarms
- White PPG paint
- Dual tailgate safety props
- Sealed body clean-outs
- Standard light package to comply with DOT and FMVSS standards
- Standard wiring package; automatic reset circuit breakers and all wiring loom protected
- Hydraulic tailgate locks with manual overlock
- Hydraulic suction line shut-off valve
- 100 MESH suction strainer
- 10 MICRON in-line return filter
- 30 GAL reservoir with internal baffles
- Sight/temperature gauge
- Crossed telescopic compactor cylinders

CHASSIS

- 7500-8500 LB standard body weights
- 25,500 (29,000-33,000) GVW minimum chassis weight

OPTIONS

EXEMPTIONS

- FET
- CDL

SAFETY

- 10 LB or 20 LB fire extinguisher
- Spill kit
- Shovel
- Camera (single, dual, hopper, and hopper mirrors)

AXLE

- Tag
- Pusher
- Steerable tag
- Steerable pusher

TIPPER

- Cart tipper (1 per trough, 500 LB capacity)

TROUGH

- Dual trough

CONTROLS

- Electric

HYDRAULICS

- 3 or 6 MICRON return line filter

ADDITIONAL CONTAINERS

Installed in front of most KANN side loaders and competitor side and rear loaders to separate additional commodity (typically recyclables)

- Side Dump plastics compactor: continuous cycle, hoist mounted lift to dump, and dump (21 YD³ of uncompacted milk jugs compacted into 1 YD³)
- Side Dump cardboard compactor: eject only
- Side Dump container
- Trough Loader™ plastics compactor (16 YD³ of uncompacted milk jugs compacted into 1 YD³)
- Trough Loader™ container

LIGHTS

- LED lights
- LED lights with strobe turn signals
- Safety work light package
- Strobe light

PAINT

- Standard PPG other than white
- Metallic
- Multi-color
- Striping



Non FET / Non CDL Side Loader has a trough cycle time of 10-12 seconds and can pack-on-the-go making route times more efficient.



Each large 0.42 YD³ side loading trough provides complete versatility of bag, bulk, and cart routes with an optional cart tipper.

Proudly built in the USA

