



## ATLONA 10 INPUTS PROFESSIONAL VIDEO PROCESSOR



Weight	4.70 lbs
SKU#	AT-LINE-PRO4

### FEATURES:

- Scaling any incoming Signal whether VGA, Composite, DVI or any other to the native resolution of the display: VGA~WUXGA or 480p~1080p
- Analog to digital AV conversion
- PAL to NTSC and NTSC to PAL conversion 50/60Hz
- Digital and analog switching capabilities with HDMI out
- RS232 commands available for control systems
- Digital coax out for connecting your audio to an AV receiver
- Learnable IR codes for universal remote controls
- Standard 1U size for easy rack mounting
- 3.5mm Audio jacks for audio embedding on HDMI inputs (the main purchase for that is DVI sources are used with HDMI/DVI adapters)
- Full 3D support on HDMI pass through
- Horizontal and vertical shift, color, tint, brightness, contrast, detail, sizing, and top and bottom vertical blanking adjustments
- HDMI 1.3c, HDCP 1.1 and DVI 1.0 compliant
- VGA Inputs Supports following Resolutions: VGA ~WUXGA or 480p~1080p
- HDMI inputs support following resolutions: 480i~1080p and VGA~WUXGA
- Supports deep color of 8 / 10 / 12 bits per color (x3)
- On-Screen-Display allows users to fully adjust inputs/outputs preferences
- 3-D motion adaptive & 3-D video noise reduction

### SPECIFICATIONS:

- HDMI Resolutions: 480i~ 1080p60 and VGA~WUXGA
- PC Resolution: VGA ~WUXGA, 480p~1080p60
- ESD Protection: Human body model: ± 8kV (air-gap discharge)  
± 4kV (contact discharge)
- Power Supply: 5V/2.6A DC (US/EU standards, CE/FCC/UL certified)
- Dimensions (inch): 17.1 (W) x 6.57 (D) x 1.92 (H)
- Weight (lb): 4.7
- Power Consumption: 8.5W
- Operating Temperature: 0°C ~ 40°C / 32°F~104°F
- Storage Temperature: -20 C ~60 C / -4°F~140°F
- Relative Humidity: 20~90% RH (non-condensing)

### REAR VIEW:



### INPUTS/OUTPUTS:

- Input Ports: 4 x HDMI (DVI), 3 x VGA, 1xS-Video, 1 x Component Video, 1 x Composite Video
- Output Ports: 1 x HDMI, 1xCoaxial

### PACKAGE CONTENTS:

- 10-Input Professional Video Scaler
- 5V/2.6A DC power adaptor
- Operations manual

### WARRANTY

3 year manufacturer warranty (parts and labor)



CONNECTION DIAGRAM

