



ATLONA 1x4 SDI/HD-SDI DISTRIBUTION AMPLIFIER WITH RE-CLOCKING TECHNOLOGY



Weight	1.50 lbs
SKU#	AT-SDI-14RC

Features:

- Supports high video bandwidth up to 1.48Gbps
- Splitter supports both SDI (SMPTE 259M) and HD-SDI (SMPTE 292M) standard
- All SDI/HD-SDI outputs are reclocked and buffered to send signal over 1000ft

Technical Specifications:

- SDI standards: SDI (SMPTE 259M) and HDSDI (SMPTE 292M)
- Detection: Automatic detection of SDI or HDSDI
- Supported formats: SMPTE 259M and SMPTE 292M
- Video Bandwidth: 1.485Gbps and 1.485/1.001Gbps
- Data rates: 270, 1483, 1485 Mbps
- HD Video Resolutions: 720p50/59.94/60, 1035i50/59.94/60, 1080i50/59.94/60, 1080p24/30
- SD Video: NTSC@59.94Hz, PAL@50Hz
- Audio Support: Yes
- Power supply: DC 5V / 4A (110/220V universal)
- Dimensions (inch): 5.7L x 3.2W x 1H
- Weight: 1.5 LB

Rear View



Inputs/Outputs:

- Inputs: 1 x BNC (75 Ohm)
- Outputs: 4 x BNC (75 Ohm)

Package Includes:

- 1x AT-SDI-14RC
- 1x 5V power adapter
- 1x User Manual

Warranty:

3 year manufacturer warranty (parts and labor)



Atlona
Tel: 408-954-8782
Fax: 408-954-8792
toll free: 1-877-536-3976

WWW.ATLONA.COM



SIMPLE, EASY

ATLONA®

Connection Diagram

HD/SD SDI Camera



AT-SDI-14RC



HD/SD SDI Display



HD/SD SDI Display



HD/SD SDI Display



HD/SD SDI Display

Atlona
 Tel: 408-954-8782
 Fax: 408-954-8792
 toll free: 1-877-536-3976

WWW.ATLONA.COM

COMPATIBLE WITH: Control UNIVERSAL® remote control

Member