

## **CURB MASTER** SERIES

## **Side Loader**



SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Low 35 inch **Loading Height** 



## **CURB MASTER SERIES**

# Side Loader

## **FUNCTION**

- · 8 sec trough cycle
- 22 sec compactor cycle
- 8 sec cart tipper
- · Pack-on-the-go

### **GENERAL**

- 23, 27, 31 YD3 body capacities
- 3 YD3 tailgate capacity
- 4 YD3 hopper capacity
- .75 YD3 trough capacity
- · 500 LB maximum trough lift capacity
- Trough loading height at chassis frame (approximately 35 IN from ground to
- 100 MESH suction strainer
- 10 MICRON in-line return filter
- 60 GAL reservoir with internal baffles
- Sight/temperature gauge
- · Single stage, double acting compactor blade cylinders
- · Tailgate ajar light/buzzer
- White PPG paint
- Tailgate safety props
  Standard light package to comply with DOT and FMVSA standards
- Standard wiring package automatic reset circuit breakers and all wiring loom protected
- Front mount pump
- · Body clean-out
- Hydraulic tailgate locks with manual overlock
- 48 GPM at 1200 RPM
- 2000 PSI operating pressure
- Double acting hydraulic cylinders
- · O-ring or JIC hydraulic fittings
- Hydraulic valve #VA35 capable of 70 GPM
- Tailgate rotates 135° to dump
- Body is tapered 6 IN front to back for easy discharge
- · Single or continuous cycle compactor; penetrates receiving container 12 IN eliminating feedback and provides ejection force
- Maintained pressure control system

## **CHASSIS**

- 54,000-66,000 GVW
- 14,000-20,000 front GVWR
- 40,000-46,000 rear GVWR

- 10 LB or 20 LB fire extinguisher
- · Camera (single, dual, hopper)

- Tag
- Pusher
- Steerable tag
- Steerable pusher

Cart tipper

## **HYDRAULICS**

- 3 or 6 MICRON hydraulic return line filter
- Transmission mount PTO

## **LIGHTS**

- LED lights
- Safety work light package
- Strobe light

## **PAINT**


- Standard PPG other than white
- Metallic
- Multi-color
- Striping

## **MISCELLANEOUS**


- Dual side loading
- On-board scales
- Tippers and troughs are interchangeable
- · Rubber flap for compactor



The large independent loading 0.75 YD3 trough and cart tipper are available on street side and/or curb side providing for complete versatility of bag, bulk, and cart routes.



A) The hinged follower cover allows for constant loading without commodity falling behind the compactor blade.



B) The follower cover extends and retracts with the blade.



The KANN SL has a smooth contoured body engineered to dump refuse easily and completely clean.