



REFUSE & RECYCLING BODY COMPANY

CURB MASTER SERIES

Single Side Loader



Load With Blade In Any Position and Pack-on-the-Go



Low 35 inch Loading Height and Up To 2 Cart Tippers

KANN Manufacturing Corporation
210 Regent Street
PO Box 400
Guttenberg IA 52052 0400
Tel (563) 252 2035
Fax (563) 252 3069
E-mail sales@kannmfg.com
Web www.kannmfg.com



REFUSE & RECYCLING BODY COMPANY

CURB MASTER SERIES

Single Side Loader



FEATURES

FUNCTION

- 10 SEC trough cycle
- 30 SEC compactor cycle
- 95 SEC full eject cycle
- Pack-on-the-go

GENERAL

- 9, 12, 14, 18, 21, 23, 27, 30, 32 YD³ body capacities
- 3 YD³ hopper capacity
- 98 IN body height above chassis frame with trough down
- 110 IN body height above chassis frame with trough up
- 96 IN body width
- 4 FT X 7 FT (28 FT²) hopper opening
- 1.8 YD³ single trough capacity
- 1200 LB maximum trough lift capacity
- Trough loading height 2 IN below chassis frame (approximately 35 IN from ground to trough edge)
- Up to 900 LB/YD³ payload
- 100 MESH suction strainer
- 10 MICRON in-line return filter
- 60 GAL reservoir with internal baffles
- Sight/temperature gauge
- 2 single stage, double acting compactor blade cylinders
- 1 telescopic, double acting eject cylinder
- 2 single stage, double acting tailgate cylinders
- 2 single stage, double acting trough lift cylinders
- Tailgate ajar/overheight, arms overheight, and hydraulic overheat alarms
- White PPG paint
- Tailgate safety props
- Standard light package to comply with DOT and FMVSA standards
- Standard wiring package automatic reset circuit breakers and all wiring loom protected
- Front mount pump
- Body clean-out
- Hydraulic tailgate locks with manual overlock
- Hydraulic suction line shut-off valve

CHASSIS

- 54,000-66,000 GVW
- 14,000-20,000 front GVWR
- 40,000-46,000 rear GVWR

OPTIONS

SAFETY

- 10 LB or 20 LB fire extinguisher
- Camera (single, dual, hopper)

AXLE

- Tag
- Pusher
- Steerable tag
- Steerable pusher

TIPPER

- Cart tipper (up to 2 per trough, 500 LB capacity)

HYDRAULICS


- 3 or 6 MICRON hydraulic return line filter
- Transmission mount PTO

LIGHTS


- LED lights
- Safety work light package
- Strobe light

PAINT

- Standard PPG other than white
- Metallic
- Multi-color
- Striping



A) The hinged follower cover allows for constant loading without commodity falling behind the compactor blade.



B) The follower cover extends and retracts with the blade.



The large 1.8 YD³ loading trough capacity and the capability to have up to 2 cart tipper mounted on the trough provides for complete versatility of bag, bulk, and cart routes.



The full eject push out panel quickly travels the full length of the body and is engineered to eject all types of refuse and recyclables easily and completely clean.