




ATLONA PROFESSIONAL STEREO/MONO AUDIO AMPLIFIER WITH 3 INPUTS (2 x STEREO, 1 x MIC)



Weight	3.00 lbs
SKU#	AT-PA100


FEATURES:

- Commercial Class-D Stereo/Mono Audio Amplifier
- 2x20Watt @ 4Ohm or 1x40Watt @ 8Ohm, amplifier could be used to amplifier 2 speakers or one speaker when in Bridge mode.
- Dual-Mono Ability. Mono could be shared between 2 speakers at a higher impedance.
- Microphone mixer function. The microphone can be mixed with line audio output, and separately controllable.
- Two stereo audio inputs and one Microphone input, switchable by front panel buttons or RS232.
- Volume/Bass/Treble controllable by front panel buttons or RS232, which makes it a perfect device for any commercial application where a 3rd party control system is used.
- Line audio output, with volume control.
- RS232 control ability includes feedbacks which will allow control panel to know whether the certain change was made or not.
- Antistatic case design: providing good protection for long-term and intermittent performance.
- Internal international power supply (100Volt~240Volt AC, 50/60Hz) for worldwide compatibility.
- Fast switching speed.
- LED indicator, for power and input status.

SPECIFICATIONS:

- Input Connector: 2 x RCA, 1 x 3.5mm, 1 x 6.5mm (Mic)
- Input Impedance: >10KΩ
- Output Connector: 1x3.5mm jack, 1xPhoenix connector, 4 pole
- Output Impedance: 50Ω/stereo, 4~8Ω/Amplifier
- Frequency Response: 20Hz ~ 20KHz
- SNR: 80 dB at maximum output
- CMRR: >70dB@20Hz~20KHz
- Bandwidth: 20Hz ~ 25KHz
- Power Output: 20 Watts X 2 (4 Ohms)
- Serial Control Port: RS-232, 9-pin female connector
- Power Supply: 24V (Universal 110/240V)

SIDE VIEW:



INPUTS/OUTPUTS:

- Inputs: 2 x Stereo Audio, 1 x Mic
- Outputs: 1 x Amplifier, 1 x stereo audio

WARRANTY

3 year manufacturer warranty (parts and labor)





CONNECTION DIAGRAM

