

Fog Nozzles

Fire Pro Fog Nozzles comply with all aspects of U.S. Forest Service Specifications. Twist shutoff fog tips are machined from high strength 6061 T-6 aluminum bar stock and have a hard anodized finish. Dual gallonage tips have durable, stainless steel deflectors. A “quick throw” pattern change from a strong impinging straight stream to a heavy uniform fog pattern with outstanding performance.



FP-1023T



FP-60CGT

Fog Tips

Model	Length (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	GPM (GPM/LPM)
FP-1023T	3 3/4 (95)	10 (5)	1 (25)	10-23 (38-87)
FP-1040T	3 3/4 (95)	10 (5)	1 (25)	10-40 (38-151)
FP-6095T	5 (127)	1-1/4 (0.5)	1-1/2 (38)	20-60 (76-227)
FP-6095TB	5 (127)	1-1/4 (0.5)	1-1/2 (38)	20-95 (76-360)
FP-60CGT	7 (178)	2-1/2 (1)	1-1/2 (38)	60 (227)
FP-95CGT	7 (178)	2-1/2 (1)	1-1/2 (38)	90 (341)
FP-125CGT	7 (178)	2-1/2 (1)	1-1/2 (38)	125 (473)

Ball Shutoffs

Ball shutoffs are machined from 6061 T-6 aluminum bar stock to be rugged and durable. Dual handle stops combined with “fast change” replacement seat feature makes them a versatile performer for all fire ground uses—simply remove the tail gasket and the rear seat and the ball will drop out. Bull shutoffs are ideal for use in combination with fog tips, for economical breakaparts, and comply with all aspects of required U.S. Forest Service Specifications.



FP-10R

Ball Shutoff

Model	Length (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	Waterway (in/mm)
FP-10R	3 1/4 (83)	1-1/4 (0.5)	1 (25)	3/4 1 (19)
FP-15	3 3/4 (95)	1-3/4 (0.8)	1-1/2 (38)	1 (25)