


THE KEITH®
M-Series DRIVE

The lightest drive unit available in the moving floor industry.



THE KEITH® KMD-175 DRIVE

The same reliable KEITH technology in a smaller drive unit. Designed for lighter loads, such as shredded paper, agricultural products, wood chips, curbside collection and manure spreaders.

- Lighter weight increases payload.
- Full-frame design and inline bolt pattern for easy installation.
- Compact design.
- Easily removable cylinder pack.
- Electric and manual operation.
- Requires less gallons per minute for same fast throughput.
- Standard, bi-directional KEITH technology.
- Optional pressure filter.

KEITH, the creator of WALKING FLOOR® technology, provides custom unloading systems for specialized applications worldwide.


WALKING FLOOR®
ONLY BY KEITH®

IDEAL FOR INSTALLATION IN

- Mobile Document Destruction Trucks
- Small Trailers
- Drop-Off Containers
- Small Bins
- Small Trucks
- Landscape Trucks
- Agricultural Equipment

**PUSH THE LIMITS.
 WE WALK ALL OVER THEM.**

KMD-175 Cylinder Pack



KMD-175

Hydraulic Drive Unit Specifications

KMD-175

Drive Features

Cylinder Bore	1.75" [44mm]
Cylinder Stroke	4.0" [101mm]
Maximum Working Pressure	3000 PSI [210 bar]
Recommended Pump flow	5.5 g/min [21 l/min]
Load Capacity	5 ton [4536kg]
Floor Speed	0-8 ft/min [0-2.5m/min]

Overall Height	4.25" [108mm]
Drive Frame Length	31 3/16" [792 mm]
Weight (24 slat system)	280 lbs [127kg]*

* Does not include flooring.



No part of drive extends below drive frame.

FEATURES

Compact Design for Easy Installation

- Small drive opening.
- Inline bolt pattern on drive shoe allows for pre-drilling of flooring.
- Nut Bar Shoe makes installing flooring a one person job.
- Smallest drive unit available.
- Lightest weight drive unit available.
- Installation can be completed by one person.

Standard Drive Features

- Automatic poppet switching valve, no adjustments necessary.
- No external plumbing.
- Longer drive shoes for more structural strength.
- Chromate finish protects aluminum components from corrosion.
- Simple, easy to remove cylinder pack.

Optional Equipment

- Electric on/off valve.
- Electric load/unload valve.
- Inline pressure filter.

WALKING FLOOR®
ONLY BY KEITH®

KEITH Mfg. Co.
WORLD HEADQUARTERS
Madras, OR USA
(541) 475-3802
sales@keithwalkingfloor.com

Canada
Brantford, ON N3S 0A9
(519) 756-9178
canadasales@keithwalkingfloor.com

México
Guadalajara, Jal.
(+52)(33) 3616 5079
mjb@keithwalkingfloor.com

Australia
Koorringal, NSW 2650
(+61)(02) 69226888
ausales@keithwalkingfloor.com

KEITH WALKING FLOOR Europe
The Netherlands
Barneveld
(+31) 342 422007
eurosales@keithwalkingfloor.com

España
Rossello (Lérida)
(+34) 973 732778
serviciopostventa@keithwalkingfloor.com

United Kingdom
Dalton, Huddersfield, West Yorkshire
(+44) 1484 317395
mallan@keithwalkingfloor.com



www.keithwalkingfloor.com

