

FasTrak™ SuperDuty 36/42

Features and Benefits

- A true, commercial-duty unit in a compact package.
- Commercial-duty ZT 3100
- SmoothTrak™ steering with patented automatic park brake system
- 20 HP Kawasaki FX engine

LIMITED
WARRANTY
4 YEAR | **800**
HOUR
RESIDENTIAL

OR

LIMITED
WARRANTY
2 YEAR | **800**
HOUR
COMMERCIAL

** See your local Hustler dealer for complete warranty details*



* LIMITED *
LIFETIME
WARRANTY
FRAME & LEADING EDGE OF DECK

** Original Purchaser Only*

hustlerturf.com

PN 600944 5-11

HUSTLER
Cutting Grass Not Corners



FasTrak™ SuperDuty 36/42 Specifications

Engines

Kawasaki FX
20 hp

More Engine Information: • www.kawpower.com

ENGINE

Starter: 12-volt, (see engine manufacturer specs)

Ignition: Electronic.

Charging System: 12-volt. (see engine manufacturer specs for current rating)

Fuel: Unleaded gasoline - maximum of 10% ethanol in fuel. (see engine manufacturer specs)

Fuel Filter: Replaceable, automotive-type.

Air Filter: Heavy duty canister air cleaner to extend the service interval for excessive, dirty applications and improved performance.

Cooling: Air cooled. Fly-wheel fan.

Governor: Mechanical.

TRACTION DRIVE SYSTEM

Type: Dual hydrostatic. Commercial-duty Hydro-Gear ZT3100.

Hydrostatic Drive: V-belt drive from engine crankshaft.

Filter: Spin-on type.

Ground Speed: Infinitely variable

Forward: 0-7.5 mph (0-12.1 kph)

Reverse: 0-4.5 mph (0-7.2 kph)

Steering: SmoothTrak™ twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and true zero-radius turns are all controlled with hand-operated controls.

Turning Radius: True zero radius. Turns within its own length. Counter-rotating, independent drive wheels.

Brakes:

Service: Hydrostatic dynamic braking.

Parking: Internal transmission mechanical brake. When steering levers are placed in open position, integral park brakes are automatically engaged.

Tires:

Front: 13 x 5.0 – 6, rib tread

Drive: 36 in: 20 x 8.0 – 10, turf tread
42 in: 20 x 10.0 – 10, turf tread

Capacities: Fuel System: 4.2 US gal (15.9 l)

GENERAL INFORMATION

Safety Features: Operator presence system connected to deck and drive clutches. Stabilizer rollers at rear of tractor.

Seat: Molded-vinyl seat with adjustable armrests. Fore and aft adjustment. Seat-pan suspension springs standard.

Construction: Mainframe is 1.5 in x 1.5 in x .188 in (3.8 cm x 3.8 cm x .32 cm) rectangular steel tubing. Drive motors mounted to .120 in (.45 cm) welded steel. Front caster wheels mounted with roller bearings on each wheel. Front caster forks are .375 in (.95 cm) steel.

Controls: Hand-operated choke/throttle, ignition switch, electric mower clutch. Integrated parking brakes.

Indicators: Hour meter.

Cup Holder: Cup holder molded into the left side fuel tank. Holds nearly any cup size.

DIMENSIONS

Height: 40 in (101.6 cm)

W/36 in Deck:

Length: 75.8 in (192.6 cm)

Overall width: 37.76 in (95.9 cm) w/discharge chute up

Tire-to-tire width: 35.3 in (89.6 cm)

Weight: 680 lbs (308 kg)

W/42 in Deck:

Length: 78.3 in (198.9 cm)

Overall width: 44.62 in (113.3 cm) w/discharge chute up

Tire-to-tire width: 38 in (96.5 cm)

Weight: 690 lbs (312 kg)

DECKS

Side-Discharge: 36" and 42"

Type: Free-floating deck using two blades. Deck is suspended at the corners. Includes deck-mounted rollers to improve flotation in rolling and uneven terrain.

Construction: 7 ga, .179 in (.45 cm) welded steel with 11 ga, .125 in doubler welded onto spindle mount areas. Solid 1.5 in x .5 in (3.81 cm x 1.27 cm) steel bars reinforce impact areas on trim edges. Steel deck housing is 4 in (10.16 cm) deep which allows high-capacity mowing.

Cutting Heights: Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (3.81 cm to 11.4 cm).

Mowing Blades: Heavy-duty, heat-treated steel.

36 in: 1-13.75 in x 2.5 in x .20 in

1-20.5 in x 2.5 in x .20 in

42 in: 2-20.5 in x 2.5 in x .20 in

Blade Tip Speed:

36 in: 18,400 fpm

42 in: 18,400 fpm

Deck Drive: Single V-belt drive from engine with electric clutch to the two spindles. Spring tension idler for extended belt life.

Spindles: Aluminum casting with steel shafts and sealed ball bearings.

Discharge Chute: High density, rubberized.

Width of Cut:

36 in: 33.5 in (85.09 cm)

42 in: 40.25 in (102.24 cm)

Trim Capacity: (left side)

36 in: 0.5 in (1.27 cm)

42 in: 2.25 in (5.75 cm)

ACCESSORIES

Mulch Kit: Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass.

Flex Forks™: Shock-absorbing front caster forks for a smooth cut and an even smoother ride.

Other Accessories: Steering Lever Extension Kit, Light Kit

Specifications subject to change without notice.