



DuraPack® 4060

Split-Body Rear Loader





DuraPack® 4060

Split-Body Rear Loader Product Specifications

Performance Specifications	
Compaction	up to 750 lbs. per yd ³
Hopper sizes	1.5 & 1.1 yd ³
Packing cycle time	15-17 seconds
Reload time	9-10 seconds

Hydraulic Specifications	
PUMP	
Type	Tandem vane
Maximum Operating Pressure	2,500 psi @ 1,300 RPM
OIL RESERVOIR	
Tank Capacity	54 gallons
Filters	3 micron return filter with in-cab filter monitor; 100 mesh reusable suction screen
VALVES	
Shut-off	Ball valve
Packing control	Spool type
Ejector and tailgate raise	Spool type

Cylinder Specifications			
BODY CYLINDERS	TYPE	Bore	
Tailgate raise and lock	(4) Double acting	in.	3.0
		mm	76.2
Packer panels	(4) Double acting	in.	4.0
		mm	102
Slide panels	(4) Double acting	in.	4.5
		mm	114
Ejector panels	(2) Double acting 4-stage telescopic	in.	6.5
		mm	1651

Body Chamber Specifications			20 yd ³	25 yd ³
Volume	curb side (60%)	yd ³	12	15
		m ³	9.1	11.4
	street side (40%)	yd ³	8	10
		m ³	6.1	7.6
Inside width	curb side	in.	48.1	48.1
		mm	1220	1220
	street side	in.	35.3	35.3
		mm	900	900
Inside height	curb side	in.	78.7	78.7
		mm	2000	2000
	street side	in.	78.7	78.7
		mm	2000	2000

Chassis Requirements		20 yd ³	25 yd ³
Minimum GVWR		62,000	68,000
GAWR	front	16,000	20,000
	rear	46,000	48,000
Minimum CT	in.	130-136	162-168
	mm	3300-3450	4110-4270
Minimum Platform	in.	181-187	213-219
	mm	4600-4750	5410-5560
Wheelbase (cab-over)	in.	153	185
	mm	3890	4700
Additional notes		<ul style="list-style-type: none"> • If CA/CT is not as recommended, contact Heil Environmental for applicable weight distribution and GVWR/GAWR requirements. • Diesel engines require full variable speed governor. 	
<ul style="list-style-type: none"> • Must have front crank drive pump provision. • Low entry C.O.E dual-drive recommended. • Any chassis sent to Heil Environmental with less than these minimum GVWR/GVAR requirements will not be mounted. 			

Body Specifications		20 yd ³	25 yd ³
Total body capacity	yd ³	20	25
	m ³	15.2	19.1
Overall length	in.	253	285
	mm	6430	7240
Overall width	in.	97	97
	mm	2460	2460
Over height above frame	in.	98	98
	mm	2490	2490
Overall height tailgate raised	in.	155	155
	mm	3940	3940
Gross weight (approximate)	lbs.	24,000	25,000
	kg	9530	9980

Tailgate Specifications			
Hopper capacity	curb side (60%)	yd ³	1.5
		m ³	1.14
	street side (40%)	yd ³	1.1
		m ³	0.84
Loading sill height below chassis frame (both)	in.	5	
	mm	51	
Hopper width	curb side	in.	43.3
		mm	1100
	street side	in.	31.5
		mm	800
Hopper opening height (both)	in.	66.5	
	mm	1690	

All designs, specifications, and components are subject to change at the manufacturer's sole discretion at any time without notice. Data published herein is for information purposes only and shall not be construed to warrant suitability of the unit for any particular purpose, as performance may vary with the conditions encountered. The only warranty is our standard written Warranty Statement for this product at the time of shipment.



2030 Hamilton Place Blvd., Suite 200, Chattanooga, TN 37421
 866.FOR.HEIL (866.367.4345) • Fax: 423.855.3478
 www.heil.com

© 2011, Heil Environmental, Printed in the U.S.A.
 FORM #SWS-000011-050211

CONTACT YOUR LOCAL DEALER