



# Hustler FasTrak™

## Features and Benefits

- Powerful Kawasaki FS engines
- 48" 54" or 60" side-discharge decks
- Welded steel decks. NOT STAMPED!
- Commercial duty ZT 3100 transmissions
- Commercial duty, serviceable deck spindles
- Toughest frame, front forks and deck in the industry
- Simplest maintenance in the industry
- Comfortable foot-operated deck-lift system - 1.5" to 4.5"
- 3.1 gallon fuel capacity
- SmoothTrak™ steering with patented automatic park brake system
- 20" drive tire, 13" caster tire
- Standard, Certified ROPS and seat belt



LIMITED WARRANTY

**4** YEAR | **400** HOUR

RESIDENTIAL

LIMITED WARRANTY

**1** YEAR | **400** HOUR

COMMERCIAL

OR

\* See your local Hustler dealer for complete warranty details

\* LIMITED \*

**LIFETIME WARRANTY**

FRAME & LEADING EDGE OF DECK

\* Original Purchaser Only

[hustlerturf.com](http://hustlerturf.com)

PN 601128 2-11

**HUSTLER**  
Cutting Grass Not Corners



# FasTrak™ Specifications

## Engines

**Kawasaki FS**  
22 hp

**Kawasaki FS**  
24 hp

**Kawasaki FS**  
26 hp

### More Engine Information:

• [www.kawpower.com](http://www.kawpower.com)

#### ENGINE

**Starter:** 12-volt, (see engine manufacturer specs)

**Ignition:** Electronic

**Charging System:** 12-volt, (see engine manufacturer specs for current rating)

**Fuel:** Unleaded gasoline - maximum of 10% ethanol in fuel (see engine manufacturer specs)

**Fuel Filter:** Replaceable, automotive-type

**Cooling:** Air cooled. Fly-wheel fan

**Governor:** Mechanical

#### TRACTION DRIVE SYSTEM

**Type:** Dual hydrostatic. Commercial-duty Hydro-Gear ZT 3100.

**Hydrostatic Drive:** V-belt drive from engine crankshaft

#### Ground Speed:

**Forward:** Infinitely variable: 0-8 mph (0-12.9 kph)

**Reverse:** 0-5 mph (0-8 kph) reverse

**Steering:** SmoothTrak™ twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls.

**Turning Radius:** True zero turning radius. Turns within its own length. Counter-rotating, independent drive wheels.

#### Brakes:

**Service:** Hydrostatic dynamic braking.

**Parking:** Internal transmission mechanical brake. When steering levers are placed in neutral position, integral park brakes are automatically engaged.

#### Tires:

**Front:** 13 x 5 – 6, rib tread

**Drive:** 48 in: 20 x 10 – 10, turf tread  
54 in: 20 x 12 – 10, turf tread  
60 in: 20 x 12 – 10, turf tread

**Capacities:** Fuel System: 3.1 US gal (11.7 l)

#### GENERAL INFORMATION

**Safety Features:** Operator presence system connected to deck and drive clutches. Stabilizer rollers at rear of tractor.

**Seat:** Molded-vinyl seat with adjustable armrests. Fore and aft sliding adjustment. Seat-pan suspension springs standard.

**Construction:** Mainframe is 1.5 in x 1.5 in x .188 in (3.8 cm x 3.8 cm x .48 cm) square steel tubing. Front caster wheels mounted with roller bearings on each wheel. Front caster forks are .375 in (.95 cm) steel.

**Controls:** Hand-operated choke, throttle, ignition switch, electric mower clutch. Integrated parking brakes.

**Indicators:** Engine warning light.

**Cup Holder:** Two cup holders molded into the left side fuel tank. Accommodates nearly any cup size.

#### DIMENSIONS

**Height:** 41.8 in (106.17 cm)

#### W/48 in Deck:

**Length:** 74.42 in (189.02 cm)

**Overall width:** 50.3 in (127.7 cm) w/discharge chute up

**Tire-to-tire width:** 47 in (119.38 cm)

**Weight:** 835 lbs (378 kg)

#### W/54 in Deck:

**Length:** 74.42 in (189.02 cm)

**Overall width:** 56.2 in (142.7 cm) w/discharge chute up

**Tire-to-tire width:** 51 in (129.54 cm)

**Weight:** 860 lbs (390 kg)

#### W/60 in Deck:

**Length:** 75.92 in (193 cm)

**Overall width:** 62.7 in (159.3 cm) w/discharge chute up

**Tire-to-tire width:** 51 in (129.54 cm)

**Weight:** 885 lbs (401 kg)

#### DECKS

**Side-Discharge:** 48" 54" or 60"

**Type:** Free-floating deck using three blades with center blade to the front. Deck is suspended at the corners. Includes 4 deck-mounted rollers to improve flotation in rolling and uneven terrain.

**Construction:** 11 ga. .120 in (.30cm) welded steel with 11 ga. .120 in (.30cm) doubler welded onto spindle mount areas. Solid 1 in x .375 (2.55 cm x .95 cm) steel bars reinforce impact areas on trim edges. Commercial-style box-section reinforced front edge.

**Cutting Heights:** Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1.5 in to 4.5 in (3.81 cm to 11.43 cm).

**Mowing Blades:** Heavy-duty, heat-treated, low-lift steel blades.

48 in: 16.5 in x 2.5 in x .20 in

54 in: 18.5 in x 2.5 in x .20 in

60 in: 20.5 in x 2.5 in x .20 in

**Blade Tip Speed:** (at 3600 RPM engine speed)

48 in: 18,600 fpm

54 in: 18,910 fpm

60 in: 18,410 fpm

**Deck Drive:** Single V-belt drive from engine with electric clutch to two spindles. Spring tension idler for extended belt life.

**Spindles:** Aluminum casting with steel shafts and sealed ball bearings.

**Discharge Chute:** High density, rubberized.

#### Width of Cut:

48 in: 47.1 in (119.63 cm)

54 in: 53.1 in (134.87 cm)

60 in: 59.1 in (150 cm)

#### Trim Capacity: (left side)

48 in: 2.0 in (5.08 cm)

54 in: 4.5 in (11.43 cm)

60 in: 5.9 in (15 cm)

#### ACCESSORIES

**2-Bag Catcher:** Commercial-duty, 7.2 bushel, rear-mounted, two-bag catcher with commercial belt-driven blower.

**Mulch Kit:** Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil

**Flex Forks™:** Shock-absorbing front caster forks for a smooth ride and smoother cut

**Other Accessories:** Light Kit, Stripe Kit, Steering Extension Kit

*Specifications subject to change without notice.*