

Direct Connect Nozzles

Direct connect nozzles provide either a heavy-body uniform fog patten or a strong impinging straight stream for greater distances. They feature ball shutoff, dual handle stops, and a full "boot style" bumper. They are ideal for field maintenance, with a "fast change" ball and seat feature and a "quick throw" straight stream to fog pattern change. Simply remove the tail gasket and the rear seat and ball will "drop out" for easy replacement. Dual gallonage models are ideal for "mop up" or to conserve water in the low range.



FP-95CG

Standard Features:

- Combination fog and straight stream
- Lightweight/strong aluminum
- Dual handle stops
- Cast aluminum handle
- Hard anodized finish – red or grey
- "Fast Change" Delrin ball and seat
- Rugged simplicity and reliability
- 1" & 1 1/2" (25 & 38 mm) inlets

Direct Connect

Model	Length (in/mm)	Weight (lbs/kg)	Inlet (in/mm)	GPM (GPM/LPM)
FP-23	7 (178)	1-3/4 (0.6)	1 (25)	10-23 (38-87)
FP-40	7 (178)	1-3/4 (0.6)	1 (25)	10-40 (38-151)
FP-60	7 (178)	2-1/2 (1)	1-1/2 (38)	20-60 (76-227)
FP-95	7 (178)	2-1/2 (1)	1-1/2 (38)	20-95 (76-360)
FP-60CG	7 (178)	2-1/2 (1)	1-1/2 (38)	60 (227)
FP-95CG	7 (178)	2-1/2 (1)	1-1/2 (38)	90 (341)
FP-125CG	7 (178)	2-1/2 (1)	1-1/2 (38)	125 (473)

Stacked tip Nozzles

Stacked straight bore nozzles consist of a series of different orifice sizes that may be unscrewed and removed or replaced in order to achieve a range of flow rates.

- Anodized aluminum construction
- 1 1/2" & 2 1/2" (38 & 64mm) inlets



FP-3230

Stacked Tip

Model	Weight (lbs/kg)	Inlet (in/mm)	Orifice Size (in/mm)
FP-3220	8 (4)	2-1/2 (64)	1-3/4, 1-1/2, 1-3/8 (44, 38, 35)
FP-3230	8 (4)	2-1/2 (64)	2, 1-3/4, 1-1/2 (51, 44, 38)
FP-3240	8 (4)	1-1/2 (38)	1-1/4, 1-1/8, 1 (32, 29, 25)