Rapid Station



Dispense PowerBoss Chemicals at 10 GPM.





10 GPM Fill Rate

- Fills autoscrubbers and mop buckets 2-4 times faster than conventional dispensing equipment.
- Requires a 3/4" incoming water supply line to produce 10 gallons per minute.

Rapid Station Includes:

- Proportioning unit
- Instructions
- 10 ft. discharge hose
- Metering tips
- 8 ft. product supply hose asm.

Rapid Station Drum Dispensing:

Assemble supply hose as shown at left, insert appropriate tip and attach supply hose to hose barb on inductor. The Rapid Station dispenser fills auto scrubbers and other large reservoirs at 10 gallons per minute (37.8 liters per minute) to reduce fill time. Unit includes a built in vacuum breaker, 6 feet of discharge hose, and metering tips to determine dilution ratio. Stainless steel cover and brass internal components offer durability and industrial appearance.

PowerBoss Chemicals

Formula 340 Heavy Duty Degreaser A powerful low foaming degreaser

Citrus Assault Citrus Degreaser A citrus fortified degreaser


Tough Green Environmental Degreaser A neutral pH degreaser. Safe to use, safe for the environment.



Installation:

REQUIREMENT: The incoming water supply must have a minimum 3/4" diameter line to produce 10 gallons per minute. The incoming water source must be a single source (cold water) line to prevent cross-connection control concerns. This unit is designed to be hard plumbed and is equipped with a 3/4 NPSF for ease of installation.

There are 4 mounting holes for installing this unit. Use enclosed hardware for mounting unit to wall. The installation location should be at least 12" above location of chemical concentrates used. Attach 1" diameter discharge hose to hose barb located on bottom of inductor and secure with hose clamp.



Operation:

- 1. Place 55 gallon drum of product near Rapid Station.
- 2. Select proper dilution tip from the chart below.
- 3. Screw the dilution tip into the product supply hose barb.
- 4. Attach the product supply hose over the end of the product supply hose barb. Insert tubing with ceramic weight and check valve into drum through bung hole and secure.
- 5. Turn water source to ON.
- Dispense product:
 - a. Direct discharge tube into scrubber tank, extractor, etc.
 - Begin dispensing chemical by turning the ON/OFF valve lever all the way to ON.
 Note: Lever must be turned on all the way to dispense concentrates in correct proportion.
 Unit will draw chemical concentrate only when water in discharge hose backs up to inductor.
 - c. Turn ON/OFF valve lever to OFF when tank is filled.

Tip Chart

| Part No. | Product | Heavy Cleaning Dilution | Tip Color | Normal Cleaning Dilution | Tip Color | Light Cleaning Dilution | Tip Color |
|----------|---------------------------------|-------------------------------|--------------|--------------------------------|--------------|-------------------------------|--------------|
| 952727 | Formula 340 HD degreaser | 1:16 | Blue | 1:32 | Black | 1:64 | Pink |
| 952757 | Citrus Assault citrus degreaser | 1:16 | Blue | 1:32 | Black | 1:64 | Pink |
| 903977 | Tough Green enviro degreaser | 1:16 | No Tip | 1:32 | Gray | 1:64 | White |

LIMITED WARRANTY

PowerBoss Division warrants to the original purchaser/user that this product is free from defects in workmanship and materials under normal use and service for a period of 90 days from date of purchase. In addition, PowerBoss Division will, at its option, honor labor warranty claims for the first 90 days from date of sale, provided such claims are submitted through and approved by factory authorized repair stations. PowerBoss Division will, at its option, repair or replace without charge, except for transportation costs, parts that fail under normal use and service when operated and maintained in accordance with the applicable operation and instruction manuals.

All warranteed items become the sole property of PowerBoss Division or its original manufacturer, whichever the case may be.

PowerBoss Division disclaims any implied warranty, including the warranty of merchantability and the warranty of fitness for a particular purpose. PowerBoss Division assumes no responsibility for any special, incidental or consequential damages.

This limited warranty is applicable only in the U.S.A. and Canada, and is extended only to the original user/purchaser of this product. Customers outside the U.S.A. and Canada should contact their local distributor for export warranty policies. PowerBoss Division is not responsible for costs or repairs performed by persons other than those specifically authorized by PowerBoss Division. This warranty does not apply to damage from transportation, alterations by unauthorized persons, misuse or abuse of the equipment, use of non-compatible chemicals, or damage to property, or loss of income due to malfunctions of the product.

This warranty gives you specific legal rights, and you may have other rights which vary from state to state. Some states do not allow the exclusion or limitation of special, incidental or consequential damages, or limitations on how long an implied warranty lasts, so the above exclusions and limitations may not apply to you.