

**Customer Service** 


◆ Tel: (800) 631-2153

◆ Fax: (888) 645-7278 www.crownengineering.com

## **TWISTED ROPE - HI TEMP**

Our ceramic fiber rope is a twisted three-ply rope made to meet tough industrial standards, **2300 degrees fahrenheit (1260 degrees centigrade)**. Typical uses include gasketing, packing and sealing applications. Our rope exhibits excellent chemical stability, resisting attack from most corrosive agents. Exceptions are Hydrofluoric and Phosphoric acids and concentrated alkalies. They also resist Oxidation and Reduction. If wet by water or steam, thermal and physical properties are completely restored upon drying. No water hydration is present.

## Ceramic High Temperature Asbestos Free Twisted Rope



DIA	FT. / Carton	Part Number
1/4"	45'	14FR45
1/4"	90'	14FR90
1/4"	900'	14FR900
3/8"	25'	38FR25
3/8"	50'	38FR50
3/8"	500'	38FR500
1/2"	15'	12FR15
1/2"	30'	12FR30
1/2"	300'	12FR300
5/8"	Sold per foot	58FR
3/4"	Sold per foot	34FR
1"	Sold per foot	1FR
1-1/4"	Sold per foot	114FR
1-1/2"	Sold per foot	112FR
2"	Sold per foot	2FR


## **BRAIDED ROPE - HI TEMP**

Our ceramic fiber braided rope is a tightly knitted braid that keeps it's form under the most extreem applications. It won't unravel or flatten and is easy to cut.

Constant operating temperature of 2300 degrees fahrenheit (1260 degrees centigrade). Typical uses include gasketing, packing and sealing applications. Our rope exhibits excellent chemical stability,

resisting attack from most corrosive agents. Exceptions are Hydrofluoric and Phosphoric acids and concentrated alkalies. They also resist Oxidation and Reduction.

## **Ceramic High Temperature Asbestos Free Braided Rope**



DIA	FT. / Carton	Part Number
1/4"	45'	14FRB45
1/4"	90'	14FRB90
1/4"	900'	14FRB700
3/8"	25'	38FRB25
3/8"	50'	38FRB50
3/8"	500'	38FRB400
1/2"	15'	12FRB15
1/2"	30'	12FRB30
1/2"	300'	12FRB200
5/8"	Sold per foot	58FRB
3/4"	Sold per foot	34FRB
1"	Sold per foot	1FRB
1-1/4"	Sold per foot	114FRB
1-1/2"	Sold per foot	112FRB
2"	Sold per foot	2FRB