



Standard Gauge Glass

Our 5/8" DIA. soda lime glass is an industry standard. Used in low steam boiler applications. Easy to cut!			MAXIMUM RECOMMENDED WORKING PRESSURE, psi	
OUTER DIAMETER	PART NUMBER	OVER-ALL LENGTH	TEMP UP TO 150° F	STEAM BOILER UP TO 425° F
5/8"	58GG08	8"	205	100 psi
5/8"	58GG10	10"	205	100 psi
5/8"	58GG12	12"	205	100 psi
5/8"	58GG14	14"	190	100 psi
5/8"	58GG16	16"	190	100 psi
5/8"	58GG18	18"	190	100 psi
5/8"	58GG20	20"	185	100 psi
5/8"	58GG24	24"	180	100 psi
5/8"	58GG30	30"	175	**
5/8"	58GG36	36"	165	**
5/8"	58GG48	48"	140	**
5/8"	58GG60	60"	120	**
3/4"	34GG08	08"	205	100 psi
3/4"	34GG10	10"	205	100 psi
3/4"	34GG12	12"	205	100 psi
3/4"	34GG14	14"	200	100 psi
3/4"	34GG16	16"	195	100 psi
3/4"	34GG18	18"	190	100 psi
3/4"	34GG24	24"	180	**
3/4"	34GG36	36"	165	**
3/4"	34GG48	48"	140	**



5/8" DIA. STANDARD SODA LIME GAUGE GLASS

8" to 12" sold in 12 packs.
14" to 36" sold in 6 packs.
48" & 60" sold individually.

This glass is widely used in low pressure steam boiler applications. Easily cut to size. Use Crown's Squeeze & Pop cutter #40420. Sizes are standard.

3/4" DIA. STANDARD GAUGE GLASS

Sold individually.

** MAXIMUM RECOMMENDED LENGTH IN THIS SERVICE IS 24"

High Pressure Gauge Glass

Our popular Schott brand Borosilicate gauge glass is very durable.			MAXIMUM RECOMMENDED WORKING PRESSURE, psi	
OUTER DIAMETER	PART NUMBER	OVER-ALL LENGTH	TEMP UP TO 150° F	STEAM BOILER UP TO 425° F
5/8"	58HP08	8"	435	320 psi
5/8"	58HP10	10"	420	315 psi
5/8"	58HP12	12"	410	305 psi
5/8"	58HP14	14"	390	295 psi
5/8"	58HP16	16"	375	285 psi
5/8"	58HP18	18"	360	280 psi
5/8"	58HP24	24"	320	255 psi
5/8"	58HP36	36"	245	**
5/8"	58HP48	48"	165	**
5/8"	58HP60	60"	150	**



5/8" DIA. HIGH PRESSURE BOROSILICATE® GLASS 3.3

Sold individually.

These are made from Schott's heat resistant Borosilicate® brand tubing. They are the most versatile and popular type used in our industry.

** MAXIMUM RECOMMENDED LENGTH IN THIS SERVICE IS 24"

Section 8 - Tools, Glass, Washers & V-Belts