

The Best gets Better...

Flow Control Fuel Oil De-Aerator

Combines the best features of today's Oil De-Aerators with a New design for the best de-aerator on the market!

The 4300 Flow Control II automatic fuel oil De-aerator represents "State of the art" technology and is manufactured in accordance with all safety regulations and is subject to factory testing.

- Provides superior flow characteristics over competitive de-aerators
- A secondary chamber and a third float double seals the vessel
- Comes with the industry's highest possible bio-fuel rating: B100
- Provides a continuous flow of preheated oil
- TUV tested #V132 2007 V1
- 5 year warranty
- Order Crown P/N: 43000

Side-by-Side Comparison	FLOW CONTROL #43000	TIGERLOOP
Bio-Diesel Compatibility	B100	B5
Number of Float	3	2
Max. Nozzle Capacity	26 GPH	20 GPH
Max. Oil Flow	58 GPH	50 GPH
Max. Return Capacity	37 GPH	30 GPH
Max. Operating Temp.	140°F	105°F
Max. Ambient Temp.	140°F	105°F
Maintenance	Recommended Replacement 20 years	Recommended Replacement 8 years

TÜV



Distributed By:



ENGINEERING CORPORATION
 PO Box 846 – Farmingdale, NJ 07727
 Phone: 800-631-2153 Fax: 888-645-7278
 Website: www.crownengineering.com