





<p>Shell Body with Outside Thread P/N: 45198 - 3/4 NPT X 1 1/8" Hex</p> 	<p>Gland Nut Assembly 1/2-14 NPT Thread P/N: 45199 - Fits over 1/2" DIA. insulators</p> 	<p>Copper Washer for 9/16 DIA. insulator P/N: 45200 - 9/16" ID X 3/4" OD X .032 tk.</p> 
<p>Copper Washer for 1/2 DIA. insulator P/N: 45201 - 1/2" ID X 23/32" OD X .032 tk.</p> 	<p>Gland Nut Assembly 1/2-14 NPT Thread P/N: 45202 - Fits over 7/16" DIA. insulators</p> 	<p>Copper Washer for 7/16 DIA. insulator P/N: 45203 - 7/16" ID X 11/16" OD X .032 thick.</p> 
<p>Gordon-Piatt Copper Filled Gasket P/N: 45292 - .575 ID X .740 OD X .075 tk.</p> 	<p>Brass Hex Stud Adaptor P/N: 45300 - .1/4" Hex X 10/32 Thread</p> 	<p>Need a special part or combination of parts? Why not give us a call? We would love to quote your requirements!</p>

Part Number: 45610

Description: C-10 Flame detector

Packaging: Carded - 5 per card

Includes:

Our flame detectors are hand crafted and tested twice. Once before assembly, and after. Look for them in our attractive strip packaging. Ideal POP area's. Please order in increments of 5.

A direct replacement in the Honeywell C554A, Honeywell replacement cell part numbers 130367, 120320 and 124607.



Specifications

- Maximum Voltage: 30 VAC
- Maximum Resistance: Min. 300 OHMS
- During Firing: Max. 1,600 OHMS
- Max. Cell Surface Temp: 180 Degrees F
- Method of Sensing: Cadmium Sulfide