

Products – AZ-480B



Overview

Max Cut Width*

48"

1219 mm

Max Cut Depth

12"

305 mm

Max Cut Speed**

4000 ft²/hr

372 m²/hr

Engine

John Deere

Horsepower

99 / 140 / 173

Weight***

7200 lb

3266 kg

Host Vehicle

Loader 2 yd

[Request Info](#)

AZ-480B

[See the Video >](#)



01 02 03



The AZ-480B harnesses the power and productivity of much larger reclaimers into a portable and affordable attachment, turning your loader into a high-powered reclamation machine. Powered by John Deere (Tier 3) Turbo Diesel engines, the AZ-480B will pulverize up to 12-inch thick asphalt in a single pass. The Asphalt Zipper® patented Versa-Mount universal bucket mounting system enables easy connection to the widest possible range of loaders. Easy to read and access controls and gauges along with active-hydraulic depth control and manual top hatch make it simple to use and maintain. Computer engineered cutter heads with replaceable bullet-head carbide tipped cutting teeth produce pulverized material with exceptional gradation that can be reused as road-base or backfill. Street patches, full road repairs, base stabilization and opening utility trenches in asphalt are just a few of its many uses. The AZ-480B transports easily on its own custom trailer behind a one-ton pickup truck.

* Other cut widths available.

** Based on average asphalt thickness up to 5-6" thick. Assumes max horsepower. Actual results may vary depending on asphalt hardness, temperature, oil content, age, desired grind, etc.

*** Weight with standard options equipped, without trailer and without fuel.

Specifications subject to change without notice.