

T E C H N I C A L I N F O R M A T I O N

Parameter	Typical values, English	Typical values, Metric
Nominal dimensions erect (external, max.) ①	90"L x 61"W x 101"H	2.28m L x 1.55m W x 2.57m H
Nominal dimensions erect (internal, min.)	80"L x 53.5"W x 92"H	2.03m L x 1.36m W x 2.34m H
Nominal dimensions collapsed (external, max.)	90"L x 61"W x 35"H	2.28m L x 1.55m W x 0.89m H
Nominal internal load volume (erect)	242 ft ³	6.85 m ³
Load capacity (if stacked)	2,000 lb.	907 kg
Load capacity (no stacking)	8,000 lb.	3,629 kg
Empty (tare) weight (typical)	725 lb.	329 kg
Recommended service temperatures (if stacked) ②	-40°F to +109°F	-40°C to +43°C
Recommended service temperatures (no stacking) ②	-40°F to +140°F	-40°C to +60°C

① All weights and dimensions are nominal, and can vary slightly from unit to unit due to manufacturing tolerances.
 ② Recommended service temperatures are based on published heat deflection values for RMs341 resin, backed by real-world COSMO container stacking tests performed in Pennsylvania and Nevada.



FEATURES

Feature	Standard	Optional
Manufactured exclusively with NOVA Chemicals' SURPASS® high-performance polyethylene resins in customizable colors	●	
Dual-side access with two-way lockable doors, tamper-resistant corner panel camlocks	●	
Integral UV protection, venting and weather-resistant design for outdoor service	●	
Roof top eye bolts (non-protruding)		●
Base-mounted tie-down D-rings (4)		●
Four-way forklift access, including hand-jack-friendly main fork tunnels	●	
Internal E-Track receptacles		●
Custom labels, stick-on or in-mold labels		●
Dual-wall rotomolded structure with integrally molded steel reinforcements; can be collapsed/erected in approximately 5 minutes	●	



Sales Office
 COSMO Container Solutions
 Inspirion Ventures Inc.
 1555 Coraopolis Heights Road
 Moon Township, PA 15108
 1-88-USE-COSMO
 (1-888-732-6766)
support@cosmocontainers.com
www.cosmocontainers.com

 is a trademark of Inspirion Ventures Inc.

The information contained herein is provided for general reference purposes only. By providing the information contained herein, Inspirion Ventures Inc. makes no guarantee or warranty and does not assume any liability, with respect to the accuracy or completeness of such information, or product results in any specific instance, and hereby expressly disclaims any implied warranties of merchantability or fitness for a particular purpose or any other warranties or representations whatsoever, expressed or implied. Nothing contained herein shall be construed as a license to use the products of Inspirion Ventures Inc. in any manner that would infringe any patent. Nothing herein shall be copied, reproduced, or otherwise used without the express written permission of Inspirion Ventures Inc.