



Part Number(s):

- 48101 (12 per case 1/2" Tk. X 2' X 3' LD) *
- 48102 (6 per case 1" Tk. X 2' X 3' LD)
- 48103 (4 per case 1 1/2" Tk. X 2' X 3' LD)
- 48104 (3 per case 2" Tk. X 2' X 3' LD)
- 48125 (24 per case 1/4" Tk. X 2' X 3' HD)


Description: Refractory boards

Packaging: Corrugated carton - 12/cs.

Includes:

1 case of LD or HD fiberboards from the above list. Our TaoFibre® high temperature ceramic fiber boards feature high temperature stability, low thermal conductivity, even density, and excellent resistance against thermal shock and chemical attack. TaoFibre® ceramic fiber board also resists oxidation and reduction. If they are wet by water, steam, or oil, physical and thermal properties are fully restored upon drying. Ceramic Fiber board is used for a variety of high temperature applications, including refractory linings, backup insulation, baffles and muffles, heat shields, combustion chambers, flue insulation, and fire protection. These ceramic fiber boards are low density for easy cutting and have a continuous temperature rating of 2300° F / 1260° C.

*NOTE: This item must ship via UPS Freight service to prevent shipping damage.



Original replacement gaskets for Beckett, Carlin, & Wayne burners

The below gaskets are the original OEM gaskets for the below specified burners.

Guaranteed to work in the application! For gasket specifications please contact the OEM directly.

Part Number: 100428

Description: Wayne flange gasket

Dimensions: 7 1/2" OD X 4" ID

Used in models: HS, HSR, & HSG



Part Number: 12484

Description: Wayne flange gasket

Dimensions: 7 3/8" OD X 4 5/16" ID

Used in models: EH, EASR, & EHA



Part Number: 3616

Description: Beckett flange gasket

Dimensions: 8 1/2" OD X 3 15/16" ID

Used in models: Universal



Part Number: 3811

Description: Beckett flange gasket

Dimensions: 6 1/4" L X 6 1/4" W

Used in models: Used in #68 Weil-McLain boilers.



Part Number: 5432

Description: Beckett flange kit

Packaging: Poly bagged & tagged

Includes: 1 ea. Flange & 1 ea. Gasket (3616)

Fits models: 99-101 CRD, G3 & EZ1



Part Number: 75016

Description: Carlin flange gasket #40287

Dimensions: 8" OD X 3 1/8" ID

Used in models: 99-101 CRD, G3 & EZ1



Part Number: 70203 - 11 oz. caulking tube

Description: Thermeez® ceramic putty

Packaging: Bulk

Includes:

1 - 11 oz. tube of Thermeez ceramic putty
 Thermeez is made of a high purity, asbestos free, aluminum oxide based ceramic with a melting point in excess of 3200° F.

It has a continuous service temperature of 3000° F.

Use for instant repairs to brick, mortar, burner blocks, insulation, furnace holders, thermocouples, etc...just apply and let dry!. Resistant to molten metals, most chemicals, oxidizing, and reducing atmospheres.

Cures in 24 hours at room temperature. Drying process can be accelerated by using a heat gun for emergency repairs. This product has a 8 - 12 month shelf life.

Properties

Base.....	AL203
Loss factor.....	0.017
Continuous service.....	3000°F
Melting point.....	3200°F
Density.....	40 - 50#/ft. ³
Specific heat.....	0.25 BTU/#°F
Dielectric constant @ 10 ³ CPS.....	1.61
Dielectric strength.....	100 volts/mil.
Freezing point.....	32°F
Thermal conductivity*.....	0.65
*BTU/Hr.°F ft. @ 500°F	

