



Part Number (s):

- 41402 - Vacuum gauge (0 to -30" Hg. - 1/8" NPT)
- 41402C - Vacuum gauge (0 to -30" Hg. - 1/8" NPT - Color)
- 41406 - Vacuum gauge (0 to -30" Hg. - 1/4" NPT)

Description: Vacuum gauges

Packaging: Individually Boxed

Includes:

1 - vacuum gauge boxed from the above list.
 Our vacuum gauges features a easy to read 2" face, is made of high impact acrylic bezel, with a 1/8" or 1/4" NPT bottom mount. Can be used in a variety of applications.



41402



41402C



41406

Part Number (s):

- 41404 - Pressure gauge (0 to 30 PSI - 1/8" NPT)
- 41405 - Pressure gauge (0 to 300 PSI - 1/4" NPT)
- 41452 - Pressure gauge (0 to 30 PSI - 1/4" NPT)
- 41456 - Pressure gauge (0 to 200 PSI - 1/8" NPT)
- 41457 - Pressure gauge (0 to 300 PSI - 1/8" NPT)
- 41466 - Pressure gauge (0 to 60 PSI - 1/8" NPT - 1 1/2" FACE)

Description: Pressure gauges

Packaging: Individually Boxed

Includes:

1 - pressure gauge boxed from the above list.
 Our pressure gauges features a easy to read 2" face, is made of high impact acrylic bezel, with a 1/8" or 1/4" NPT bottom mount. Can be used in a variety of applications.



41404



41405



41452



41456



41457



BACK MOUNT
41466

Part Number (s):

- 41460 - Tridicator gauge (Short stem 2.48" Long)
- 41462 - Tridicator gauge (Long stem 3.62" Long)

Description: Tridicator / Boiler gauges

Packaging: Individually Boxed

Includes:

1 - tridicator gauge from the above list.
 Our tridicator gauges features a easy to read 2 1/2" face, is made of drawn steel with corrosion resistant paint, center back mounting and a high impact polycarbonate window with chrome plated steel ring, with a 1/4"-18 NPT thread. Specifically designed to withstand conditions normally encountered in domestic hot water heating systems. Dual temperature ratings are: 60° F to 320° F / 20° C to 120° C and the pressure range is 0 to 75 PSI. It can be used in a variety of applications.



Part Number: 41463

Description: Thermometer with spud well

Packaging: Individually Boxed

Includes:

1 - Thermometer individually boxed.
 Our thermometer has an easy to read 2 1/2" face, is made of drawn steel with corrosion resistant paint, center back mounting and a high impact polycarbonate window with chrome plated steel ring, with a 1/2" NPT removable brass well (2" long from back plate of gauge). Specifically designed to withstand conditions normally encountered in domestic hot water heating systems. Dual temperature ratings are: 32° F to 248° F and 0° C to 120° C. It can be used in a variety of applications.

