## 9510 / 9512 LIQUID CRYSTAL DISPLAY 8 DIGIT COUNTER



Count total flow of any Reed Contact equipped Water, Condensate, Oil meter, etc. with the battery powered Remote Reading Counter.
Simple wiring - just two wires, not polarity sensitive with a Reset jumper located on side. 8 year battery life. The 9510 / 9512 can be wired up to 25 feet away from the Flow Meter. There are two models available in NEMA 1 or NEMA 4X enclosures.



#9510 No Reset - 8 Digits #9512 With Front Reset -8 Digits Option #9132 NEMA 4X Enclosure

**Specicications** 

**Power:** Internal lithium battery – 8 years (at 20C) **Display:** 8 digit black LCD, Digit size 0.315" high

Temperature Range:

Operating: -14 to 140°F (-10 to 60°C) Storage: -4 to 140°F (-20 to 60°C)

Signal Input:

- a) SLOW SPEED for Contact closure, 30 Hz maximum speed Negative edge triggered. Minimum pulse 15 mS.
- b) Reset external via dry contact. 0.7 V threshold. Minimum pulse 50 mS.

Approvals: CE Material: ABS Plastic

Connection: 8 pin terminal block supplied on counter

Reset Jumper hidden on side

**Sealing:** Optional NEMA 4X/IP65 Enclosure **Housing:** 4" x 2-7/8" x 2-1/2" (WxHxD)

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



ISTEC CORPORATION 5 Park Lake Road, Sparta, NJ 07871 973 383 9888 (Phone) 973 383 9088 (Fax) Email: sales@istec-corp.com

Web: www.istec-corp.com