



**Part Number(s):**

41415-48 (Case of 48 filters with gaskets)  
 41415-12 (Economy case of 12 filters with gaskets)

**Description:** String Cotton filter elements

**Packaging:** Bagged w/gasket in corrugated carton

**Includes:**

48 or 12 - Individual filters with gaskets.  
 Made for domestic fuel oils. Made of all wool string. This 40 micron rated filter removes impurities that might hamper the burner's operation. Replaces FB-4 elements.



**Part Number(s):**

41439 (Complete UL listed filter system - Individually Pkg.)

41439-06 (Complete UL listed filter system - 6 Pack)

**Description:** Complete UL listed filter system

**Packaging:** Individually boxed

**Includes:**

1 - Individually boxed filter system or

1 - 6 pack of boxed filter system.

Our newly designed Quick Spin III™ filtration system is now better than ever! It's the filter style of the future with our new triple leak protection shell that is tin plated carbon steel, epoxy coated, and an internal plastic base to prevent rust-out bottoms that other comparable filters are prone to.

As always our triple leak protection filter head is made of casted aluminum and incorporates a post gasket seal, a ridged rim that grips the seal gasket, and an outer lip that encloses the entire unit...safety first! And don't forget the practical benefits like a flat bottom, so your can doesn't spill oil all around the floor.

Our wholesale distributor's like the flat bottom design because they stack easily and our kit variety means they can offer a wider range of filtering combinations to meet their customers needs.

To top it off our Quick Spin III™ filtration system is UL listed for use in the USA and Canada with superior 10 micron filtration that effectively removes rust, scale, and other microscopic impurities that might hamper burner operation.

**UL listed for use in USA and Canada**



UL file: MH25548  
 UL Style: 41439



**Filter Characteristic's for 41439**

Canister type.....Carbon steel, tin plated & epoxy coated

Melting point.....1100°F

Certification.....UL & CUL Listed

Micron Rating.....10

Dimensions.....4 5/8" H x 3 7/16" DIA

Rated flow rate.....25 USgph

Filtering area.....550 square inches

Rated work psi.....12 P.S.I.

Filtering media.....Resin treated cellulose

Rated work temp.....Up to 140°F

Max. working psi.....35 P.S.I.

UL file number.....MH 25548

UL Style.....41439

**Our 41439 Filter Replaces or fits:**

**Crown:** Quick-Spin I & II

**Garber:** 11V-R

**Mitco:** 290M and 264-91M

**Nozzle Guard:** NG-3300-G

**Sid Harvey:** 290-6 and 264-91

**Westwood:** F100-10

**Wix:** 24100



**Part Number(s):**

41436 (Individually boxed element w/gasket)

41436-06 (6 pack of individually boxed element w/gasket)

**Description:** Replacement element only (80000850)

**Packaging:** Individually boxed w/gasket & 6/pack ctn.

**Includes:**

1 - Individually boxed filter element with gasket or

6 - Individual boxed filter elementd with gasket in carton

Designed for superior filtration, 10 micron!

Our Quick Spin III™ replaces Gar-Ber's® R cartridge and mounts on existing Gar-Ber® heads, or you can use our own (see part number 41437).



UL file: MH25548  
 UL Style: 80000850

