



SUPER & EXTREME DUTY

Flail & Rotary Mowers

Extreme
Duty



Triple Flail

Extreme
Duty



Twin Rotary

DURABILITY INNOVATION

COMMITMENT

Flail Mowers

SUPER DUTY	SIDE	FRONT/REAR	TWIN	TRIPLE
Cutter Widths*	63", 75"	75", 90"	63"/90" or 75"/90"	63"/90"/63" or 75"/90"/75"
Cutter Height*	1 1/2" to 7 1/2"	1 1/2" to 7 1/2"	1 1/2" to 7 1/2"	1 1/2" to 7 1/2"
Cutting Assembly	Dynamically Balanced - 4 3/4" Diameter Steel Tubing Cutter Shaft Standard or Reverse Rotation Available			
Knife Swing Circumference	47 7/8"	47 7/8"	47 7/8"	47 7/8"
Knife Options:				
Standard	64 to 80	80 to 96	160 to 176	224 to 256
Smooth	32 to 40	40 to 48	80 to 88	112 to 128
Tractor HP Minimum Requirements	40 HP	40 HP	60 HP	65 HP

EXTREME DUTY	SIDE	FRONT/REAR	TWIN	TRIPLE
Cutter Widths*	60", 75", 90"	75", 90", 96", 102"	60" or 75" or 90"/102"	Any Side/102"/Any Side
Cutter Height*	-1/2" to +6"	-1/2" to +6"	-1/2" to +6"	-1/2" to +6"
Cutting Assembly	Dynamically Balanced - 6" Diameter Steel Tubing Cutter Shaft Standard or Reverse Rotation Available			
Knife Swing Circumference	58 1/2"	58 1/2"	58 1/2"	58 1/2"
Knife Options:				
Standard	64 to 96	80 to 112	160 to 208	240 to 424
Smooth	32 to 48	40 to 56	80 to 104	120 to 152
Tractor HP Minimum Requirements	45 HP	45 HP	65 HP	70 HP
Safety Discharge Flaps	Rubber on Rear, Optional Steel on Front			
Mower Controls	Electric Solenoid Operated, Non-Restrictive, Starter Lockout Switch Maximum of 7 Second Shutdown			

Side-Rotary

	TSR-60C	TM-60C	TM-72C
Cutting Width*	60" Actual Cut	60" Actual Cut	72" Actual Cut
Cutting Height*	1 1/2" to 7 1/2"	1 1/2" to 7 1/2"	1 1/2" to 7 1/2"
Spindle Drive	Direct Spline	Direct Flexible Coupler	Direct Flexible Coupler
Cutter Assembly	One-piece formed dish type with one-piece forged spindle assembly.		
Cutter Head Arc	180° on Cable Lift and 159° on Combo Draft Beam.		
Knives	Two full swinging high suction heat treated knives standard. Optional three, four or six knives available.		
Lift Control	Tractor Hydraulic or Optional Cable control and valves.		

Rear Rotary (Twin)

	TSR-60R	TM60R
Cutting Width*	60" Actual Cut	60" Actual Cut
Twin Cutting Width*	60"/60"	60"/60" or 72"/60"
Cutting Height*	1 1/2" to 7 1/2"	1 1/2" to 7 1/2"
Spindle Drive	Direct Spline	Direct Flexible Coupler
Cutter Assembly	One-piece formed dish type with one-piece forged spindle assembly.	
Knives	Two full swinging high suction heat treated knives standard. Optional three, four or six knives available.	
Mount	Cat II 3-point hitch	
Cutter Head Tilt	Hydraulically adjustable up to 15°	
Lift Control	Tractor's 3-point hitch	

Tiger-Flail

QUALITY

Whether you are mowing thick grass, brush or weeds along the roadside, or leaving a finished cut at the ball fields Tiger has the Flail mowing system for your application.



SUPER DUTY FRONT FLAIL



Optional:
Transport
Egress System
Available

Reverse Rotation Shield
Meets: SAE J1001 Foot Probe
Standard

Tiger-Rotary

CRAFTSMANSHIP

Tiger's TSR Series of domed top rotary cutters help to shed debris while cutting mature vegetation.



ROTARY

Loader
Available

Multiple
Offset Hitch
Positions

Direct
Motor Drive

Domed Top Deck

Front & Rear
Safety Guarding
Standard



CUTTING POWER

Make your heavy mowing jobs easy with Tiger Flails. A perfect solution for your vegetation maintenance needs.



6" Cutter Shaft Standard on Extreme Duty

80,000 PSI Material High Impact Cutter Deck Design

Side Flail Powered by Gear Pump System



TRANSPORT

Move safely and easily as side unit stores vertical with travel locks.

VERSATILITY

Tiger Rotary Mowers will cut grass, brush and time. These versatile mowers are built for performance and durability.



3 PT. TILT CYLINDER

Allows the mower to follow the contour of the road shoulder.



Side & Rear Rotary Powered by Twin Gear Pump System

Forged Spindle Design



TRANSPORT

Move safely and easily as side unit stores vertical with travel locks.