



**Part Number(s):**

- 40630 (12" test leads)
- 40631 (18" test leads)
- 40632 (30" test leads)

**Description:** Test leads

**Packaging:** Poly bagged & tagged

**Includes:**

1 pack contains 2 leads, one red, one black. Our test leads are coated with a soft flexible vinyl cover. Our leads feature protector boots for added protection against accidental shock. Tips are of a jagged tooth design for maximum electrical contact and extra thick 18AWG UL wire.



**LOW VOLTAGE  
18 AWG**

**Part Number:** 40634

**Description:** Test leads

**Packaging:** Poly bagged & tagged

**Includes:**

1 - 8' test lead with red & black split. Made of flexible rubber insulation this test cord features 20 amp. test clips, color coded vinyl insulators for shock protection, and jagged edged jaws for a positive connection.



**110 volt**

**Part Number(s):**

- PS250 (25' reel for re-packaging)
- PS100 (100' reel for re-packaging)

**Description:** Cable Reels

**Packaging:** Bulk

**Includes:**

1 - Reel of selected sizes above  
 We are always looking for ways to save our customers money! You can save big on buying our GTO & Silicone cable in 500' spools then re-packaging them yourself as needed onto our 25' & 100' spools listed above.



**Part Number(s):**

- 41650 - 25' reel
- 41652 - 100' reel
- 41654 - 500' reel
- 41656 - 1000' reel

**Description:** 7mm GTO-15 cable

**Packaging:** Plastic or wooden reels

**Includes:**

1 - Spool of GTO-15 cable  
 Our TUF-HIDE MINI SUPERFLEX® GTO-15 cable is made of solid thermoplastic elastomer. Applications include: Transformer cable leads, ignition leads, and wire connections. UL and CSA listed.



**Specifications**

**Wire Color:** Black

**Wire gauge:** 14 AWG

**Stranding:** 19 x .014" bare copper

**Insulation Thickness:** .098"

**Temperature rating:** 105 degrees centigrade (221 deg. F)

**Voltage:** 15 KVAC

**O.D.:** .270" +/- .002

**UL style:** E - 135239

**CSA style:** 74278

**Part Number(s):**

- 41660 - 25' reel
- 41661 - 100' reel
- 41662 - 500' reel

**Description:** 7mm Silicone cable

**Packaging:** Plastic or wooden reels

**Includes:**

1 - Spool of silicone cable  
 An advanced silicone rubber insulated ignition wiring material. Used in ovens, furnaces, air conditioning equipment and other gas fired appliances. It has been found acceptable in ignitor devices tested by the American Gas Association Laboratories. UL listed.



**Specifications**

**Wire Color:** Red

**Voltage:** 25 KVDC / 10KVAC / 60HZ

**Wire gauge:** 18 AWG

**Stranding:** 16/30 nickel plated copper

**Insulation Thickness:** .113"

**Temperature rating:** 250 degrees centigrade (482 deg. F)

**O.D.:** .274" +/- .002

**UL file:** E - 96824

**UL style:** 3257

**Empty Plastic spools are available**

For 25' reel use P/N: PS250

For 100' reel use P/N: PS100