

Bronze Wye Strainer

DESCRIPTION:

The APOLLOXPRESS™ Model YB-PR (59 Series) Strainers with quick Press connections are designed to protect domestic water systems and process equipment from unwanted foreign particles with minimal pressure loss. The valves are built for long reliable service with proven ASTM grade materials and stainless steel strainer. Features Leak Before Press® technology and 250 psig maximum working pressure.

FEATURES:

- Fast, Reliable, Economical Press Installation
- Ridgid® XL Press Tool Compatible
- Leak Before Press® Technology
- Self-Aligning Screen Design
- Blowout Ball Valve Option
- CRN OE8959.5C
- **Made in USA**, ARRA Compliant

PERFORMANCE RATING†:

- Maximum Pressure: 250 psi (17.2 bar) non-shock
- Temperature Range: 0°F - 250°F (-18°C - 121°C)

† APOLLOXPRESS connectors are designed for direct mechanical connection to ASTM B88-Type K, L, and M copper tubing in the hard drawn condition. Press connectors are not suitable for steam or flammable gas service.

MATERIAL SPECIFICATIONS:

Part Name	Material
Body	Cast Bronze, ASTM B584
Cap	Brass, ASTM B16
Connector Housing	ASTM B16 Brass
Connector O-Ring	NSF grade EPDM
Screen	302 Stainless Steel
Cap Seal (1/2")	Teflon® O-Ring
Cap Seal (3/4" - 2")	PTFE Gasket

APOLLOXPRESS™



DIMENSIONS (IN)

Model Number	Item Number	Size	Length	Cv	Wt (lbs)
YB-12PR	59-00301PR	1/2"	4.75"	5	1.0
YB-34PR	59-00401PR	3/4"	6.1"	15	2.0
YB-1PR	59-00501PR	1"	7.25"	28	3.0
YB-114PR	59-00601PR	1-1/4"	7.62"	55	3.8
YB-112PR	59-00701PR	1-1/2"	8.25"	70	5.7
YB-2PR	59-00801PR	2"	10.3"	99	7.7

For liquids, the flow coefficient - Cv - expresses the flow capacity in gallons per minute (GPM) of 60°F water with a pressure drop of 1 psi (lb/in²).

OPTIONS (SUFFIX)

- (01) – 50 Mesh (Standard 1/2" models)
- (01) – 20 Mesh (Standard 3/4" - 2" models)
- (02) – Tapped Cap
- (P2) – Tapped Cap with Plug
- (06) – Tapped cap with Ball Valve
- (E1) – 20 Mesh (for 1/2" model)
- (A1) – 40 Mesh
- (B1) – 60 Mesh
- (C1) – 80 Mesh
- (H1) – 100 Mesh

