

ALL PRODUCTS CATALOG

Backflow Preventers

4A-100 SERIES – MODEL DC-4A



Bronze body double check assembly with top access check valves and test cocks. Features captured spring cartridges and Apollo ball valve shutoffs with stainless steel trim. Contact local representative or factory for approvals. Sizes 1/2"-2".



4A-200 SERIES – MODEL RP-4A



Bronze body reduced pressure principle backflow assembly with top access check valves and test cocks. Features captured spring cartridges and Apollo ball valve shutoffs with stainless steel handles and trim. Contact local representative or factory for approvals. Sizes 1/2"-2".



4A-100 SERIES – MODEL DC-4A



Double Check Valves in sizes 2-1/2"-12". Stainless steel bodies 2-1/2"-8", FDA Approved epoxy-coated ductile iron 10" and 12". Patented TriForce™ checks in all sizes for low head loss and short lay length. Available shutoffs: monitored butterfly valves with supervisory switch, OS&Y and NRS gate valves. Horizontal and vertical installation approvals.



4A-200 SERIES – MODEL RP-4A



Reduced Pressure Principle Backflow Preventers in sizes 2-1/2"-12". Stainless steel bodies 2-1/2"-8", FDA Approved epoxy-coated ductile iron 10" and 12". Patented TriForce™ checks in all sizes for low head loss and short lay length. Available shutoffs: monitored butterfly valves with supervisory switch, OS&Y and NRS gate valves. Horizontal installation approvals.



4AN-100 SERIES – MODEL DC-4AN



Double Check Valves in an "n" flow pattern in sizes 2-1/2"-12". Stainless steel bodies 2-1/2"-8", FDA-Approved epoxy-coated ductile iron 10" and 12". Patented TriForce™ checks in all sizes for low head loss and small footprint. Available shutoffs: monitored butterfly valves with supervisory switch, OS&Y and NRS gate valves. Vertical up/vertical down installation approvals.



4AN-200 SERIES – MODEL RP-4AN



Reduced Pressure Principle Backflow Preventers in "n" and vertical up flow patterns in sizes 2-1/2"-12". Stainless steel bodies 2-1/2"-8", FDA-Approved epoxy-coated ductile iron 10" and 12". Patented TriForce™ checks in all sizes for low head loss and small footprint. Available shutoffs: monitored butterfly valves with supervisory switch, OS&Y and NRS gate valves. Vertical up/vertical down and vertical up/vertical up installation approvals.




4A-600 SERIES – MODEL DCDA-4A



Double Check Detector Assemblies in sizes 2-1/2"-12". Stainless steel bodies 2-1/2"-8", FDA-Approved epoxy-coated ductile iron 10" and 12". Patented TriForce™ checks in all sizes for low head loss and short lay length. Available shutoffs: monitored butterfly valves with supervisory switch, OS&Y and NRS gate valves. Horizontal and vertical installation approvals.



4A-700 SERIES – MODEL RPDA-4A



Reduced Pressure Detector Assemblies in sizes 2-1/2"-12". Stainless steel bodies 2-1/2"-8", FDA Approved epoxy-coated ductile iron 10" and 12". Patented TriForce™ checks in all sizes for low head loss and short lay length. Available shutoffs: monitored butterfly valves with supervisory switch, OS&Y and NRS gate valves. Horizontal installation approvals.



4AN-600 SERIES – MODEL DCDA-4AN



Double Check Detector Assemblies in "n" flow pattern in sizes 2-1/2"-12". Stainless steel bodies 2-1/2"-8", FDA-Approved epoxy-coated ductile iron 10" and 12". Patented TriForce™ checks in all sizes for low head loss and small footprint. Available shutoffs: monitored butterfly valves with supervisory switch, OS&Y and NRS gate valves. Vertical up/vertical down installation approvals.



4AN-700 SERIES – MODEL RPDA-4AN



Reduced Pressure Detector Assemblies in "n" and vertical up flow patterns in sizes 2-1/2"-12". Stainless steel bodies 2-1/2"-8", FDA Approved epoxy-coated ductile iron 10" and 12". Patented TriForce™ checks in all sizes for low head loss and small footprint. Available shutoffs: monitored butterfly valves with supervisory switch, OS&Y and NRS gate valves. Vertical up/vertical down and vertical up/vertical up installation approvals.

