

# ALL PRODUCTS CATALOG

## WYE Strainers

### 59/59LF SERIES – MODEL YB



Cast bronze body with 304 stainless steel screen; 400 CWP psig rating; wide variety of mesh screens available. Optional blow-out plug tapping. Sizes: 1/8" to 4". UL listed models available in sizes 1/8" to 1/2".



### 59/59LF-300 SERIES – MODEL YBS



Compact corrosion resistant bronze solder end Y-strainers with stainless steel screens. Generous socket wall thickness assures high strength solder joints. Pressures to 400 CWP psig. Sizes: 1/2" to 2".



### 59-V SERIES – MODEL YVB



Ideal for OEM applications where space is a premium. Corrosion resistant body and cleanout cap with standard 50 mesh stainless steel screen. Other screen sizes available. Rated 400 psig at 210°F CWP and 125 psig at 350°F WSP. Sizes: 1/4" NPT.

### 61203 SERIES – MODEL YSS



Cast CF8M stainless steel body with 304 stainless steel screen. Rated at 600 psig for 1124°F steam and 1440 psig for CWP. Screen cover is NPT tapped for blow-off connection. Sizes 1/2" to 1".

## Apollo International Strainers

### MODEL YCT



Class 250 FNPT cast iron body with 304 stainless steel screen. Rated 250 psig at 406°F steam and 400 psig at 150°F CWP. Screen cover is NPT tapped for blow-off connection. Sizes 1/4" to 3" NPT.

### MODEL 125YF



Flanged cast iron bodies with 304 stainless steel screens. ANSI Class 125. Sizes from 2" to 16" and pressure ratings to 150 psig. Screen cover has a tapped and plugged blow-off connection. Optional FDA grade epoxy coating.

### 61202 SERIES – MODEL YCS



FNPT cast carbon steel body with 304 stainless steel screen. Rated at 600 psig at 839°F steam and 1480 psig at 100°F CWP. Screen cover is NPT tapped for blow-off connection.