## **Model CP-3 Container Transport**



Introducing the CP-3, Petersen's newest Lightning Loader® system. This model was designed to add efficiency to the container transport process - save on fuel and labor costs while moving more cans in less time!

Carries three large containers at once, or multiple smaller ones.





- Standard Features
- Specifications
- Options
- Watch a Video





2.

6.

18



- 1. **CONTROL OPTIONS:** Greaseless dual walk-thru controls operational from either side of truck. Petersen also offers QUADSTICK® controls and stationary top mount controls with joysticks or valvehandles.
- 3. **OUTRIGGER STYLE:** Out and down outriggers improve safety in traffic and reduce damage to streets. 4.
- 5. **NO EXPOSED GEARS:** Boom swing does not have any exposed pinion or bull gears. Petersen's rotary actuator boom swing method is lower maintenance.
- 7. **TELESCOPIC TIP EXTENSION:** Four foot tip extension adds flexibility and maneuverability. Tip extension hoses are enclosed and protected.
- SINGLE POINT OF RESPONSIBILITY: Petersen Industries manufactures and installs both the grapple loader, including bucket and controls, and the trash dump body.
  10.
- 11. **HEIGHT:** The standard dual walk-thru has an overall height of 11'3".
- 13. **SAFETY LOCKING VALVES:** Boom cylinders have counterbalance valves, and outrigger down cylinders have pilot operated check valves to prevent leakdown or collapse in the case of hose rupture.
- 15. **BUCKET ROTATION:** Continuous rotation for convenience.
- 17. **NO HOSES BELOW BUCKET ROTATOR:** Reduced downtime due to elimination of hoses in bucket jaw area.
- 19. **ANTI-SCALPING:** Reverse curve motion of bucket helps prevent scalping of lawns. 20.
- 21. **WARRANTY:** Three year structural, one year hydraulic.